

# 代理加盟上苑墙衣外墙腻子粉招玉田县经销商

产品名称	代理加盟上苑墙衣外墙腻子粉招玉田县经销商
公司名称	美丽佳建材（北京）有限公司
价格	面议
规格参数	品牌:0 基本投资额:0-0.5万（元） 保证金额:0（元）
公司地址	北京北京市朝阳区北京市朝阳区朝阳路8号
联系电话	86 010 4006007707 13911728968

## 产品详情

上苑墙衣外墙腻子粉招玉田县经销商

上苑墙衣外墙腻子粉招玉田县经销商

上苑 墙衣 柔性抗裂外墙腻子说明 上苑柔性抗裂外墙腻子是一种经济实用型墙面找平材料。适用于室外砖混砂浆墙面，瓷砖翻新墙面批刮找平。柔韧抗裂，和易性好，施工性能优异，不会与任何涂料起反应。主要成份：石英沙、白水泥等和进口添加剂。消耗量：理论上2公斤柔性抗裂外墙腻子可以批刮一平方米（两遍）。实际用理因施工方法，墙面平整度的不同而不同。搅拌：水的加入量以施工稠度为准，搅拌均匀后，放置10分钟，再进行搅拌即可使用。不可以加入其他材料混合使用。基层处理：基层坚实无浮灰和污物，墙体表面含水率低于5%。如果墙面平滑或疏松，需进行表面处理，待干后方可批刮821刮墙腻子。批刮找平：腻子找平应在半干状态下（用的轻压不变形）完成，固化后可用砂布找平。批刮腻子厚度应大于0.5mm（夏委），腻子批刮厚度超过2mm应分次批刮，每次批刮厚度不超过2mm。批刮过厚易出现干缩开裂。执行标准：技术标准：jg/t3049（y）：环保标准：gb18582-2001。施工温度：施工环境温度5度以上，固化过程温度不低于0度。贮存和运输：存放阴凉干燥处，保持期6个月，产品无毒不燃，贮存运输可按（非危险品规则）办理。shangyuan rou xing kang lie wai qiang ni zi for interior wall is an economic and effective wall surface leveling material,used for scrap-ing and leveling of brick&concrete wall surface.thpure white putty enjoys high placeability and unique workability.lacquer putty,which has passed the certification for china environment label product,is recognized as an environment-friendly green product.principal components:gypsum,calcium carbonate and additives.consumption:theoretically,one-kilogram putty can cover an area of one square meter(twice)the actual consumption varies with the construction method and smoothness of the wall surface.mixing:the quantity of water added depends on the consistency applied.put it aside for 10 minutes after mixing it evenly . stir it again and it is ready to serve. no other materials are allowed to mix with it for use .base:treatment:the base should be solid ,and free from dust and dirt, the water content of the wall surface should be under 5%.if the wall surface is smooth or loose, wall sticker jc500 should be applied for interface treatment.scraping and leveling:the putty should be made level when it is in a semi-dry state(i.e.until no distortion appears when it is slightly pressed with hand).after being solidified, it can be made level with abrasive cloth. the thickness of putty scraped should exceed 0.5mm.applicable standard:technical standard:jg/t3049(y):quantity limitation standard of hazardous

materials gb18582-2001 construction temperature: construction ambient temperature should be above 5°C and the temperature during the solidification should be on less than 0°C. storage and transportation: kept in a cool and dry place. service life is 6 months. the product is nontoxic and noncombustible. refer to the rules of non-hazardous goods for storage and transportation.

自动灌装，自动称重，误差在500g以内。

美丽佳自有（北京、重庆）两大工厂，自有大型仓库，货源充足

自有实验板房，品质保证

本产品的品牌是0，基本投资额是0-0.5万（元），保证金额是0（元），加盟费是0（元），项目区域要求是全国，项目类别是壁纸代理加盟，计量单位是千克