

# 拓普康GTS250全站仪

产品名称	拓普康GTS250全站仪
公司名称	陕西德瑞特工贸有限责任公司
价格	面议
规格参数	加工定制:是 品牌:拓普康 型号:GTS250
公司地址	西安市雁塔区太白南路216号嘉天国际10803室
联系电话	029-82258180 13917821858

## 产品详情

品牌: 拓普康

型号: gts250

货号: gts250

颜色分类: gts255 gts252

装修及施工内容: 测绘测量

specifications for the topcon gts-255 total station (5-second)generalweight10.8 lbs (4.9 kg)dimensions7.2 in x 6.8 in x 13.2 in (18.4 cm x 17.2 cm x 33.6 cm)protection classip54 (protected against dust and water splashes)internal memory24,000 pointsangle measurementmeasuring method/reading systemabsolute encoderdetection methodhorizontal: double, vertical:singleminimum reading1-second/5-secondaccuracy5-secondddiameter of circle71 mmdistance measurementunit of measure (distance display)m/ftedm accuracy (precision)  $\pm$  (2mm + 2ppm x d)minimum reading900 m (3,000 ft)tilt sensor/compensatorrange  $\pm$  3typeautomatic vertical and horizontalmethodliquid surface reflective profile sensor readingsetting accuracy1 arcsecbattery/powerpower sourcechargeable ni-mh batterybattery life9 hoursbattery life alertyesvoltage7.2voptical plummetimageerectmagnification3xfield of view5 degreesfocus range0.5 m to infinitylevelplate/tubular bubble vial30 seconds per division/(2 mm)circular bubble vial10 minutes per division/(2 mm)telescope length of tube150 mmimageerectdiameter of objective lens (aperture)1.77 in (45mm) edm: 1.97 in (50 mm)magnification30xfield of view1 degree 30 arcminresolving power3.0 arcsecminimum focus distance1.3 m (4.2 ft)reticle illuminationprovideddisplay and keypadtype2 screen, dot matrix graphic lcd displaykeysalphanumericbacklightyestemperatureoperating-4fo~122of (-20oc~50oc)applicationsurveying and constructionyesmapping and gis (geographic information systems)yesutilitiesyesenvironment studiesyesgeomarkinyesarchaeologyyesaccident reconstructionyesmeasurement range (under fair weather

conditions)single prism2,300 m (7,500 ft)triple prism3,100 m (10,200 ft)mini prism900 m (3,000 ft)functionscoordinate measurement pointyesangle and distance stake outyesstake out lineyesoffsetsyesmissing lineyesremote elevationyesresectionyesarea calculationyesmeasurement timefine1 mm: 1.2 seconds (initial 4 seconds); 0.2 mm: 2.8 seconds (initial 5 seconds)tracking0.4 seconds (initial 3 seconds)interfacepin port9-pin (rs-232c)

本产品的加工定制是是，品牌是拓普康，型号是GTS250，规格是GTS252,GTS255