



0d31fte02cc4nf00d31fte02cc4ng00d31fte02cc4vf00d31fte04cc4nf00d31fte04cc4nf08d31fte06cc4nf00d31fwa31cc4nlw0d31fwa32cc1nlw0d31fwa32cc4nlw0d31fwb31cc1nlw0d31fwb31cc4nlw0d31fwb31cc4nxw0d31fwb32cc1nlw0d31fwb32cc2nlw0d31fwb32cc2vlw0d31fwb32cc4nlw0d31fwb32cc4nxw0d31fwb32cc4vlw0d31fwe01cc1nlw0d31fwe01cc2nlw0d31fwe01cc2nlw8d31fwe01cc4nlw0d31fwe01cc4nlw8d31fwe01cc4nxw0d31fwe01cc4vlw0d31fwe01cc5nlw0d31fwe01cc5nxw0d31fwe02cc1nlw0d31fwe02cc1nxw0d31fwe02cc1vlw0d31fwe02cc2nlw0d31fwe02cc2vlw0d31fwe02cc4nlw0d31fwe02cc4nxw0d31fwe02cc4vlw0d31fwe02cc4vxw0d31fwe02cc5nlw0d31fwe02cc5nxw0d31fwe02ec4nkw0d31fwe03cc4nlw0d31fwe03cc4nxw0d31fwe04cc4nlw0d31fwe05cc4nxw0

本产品的加工定制是是，级数是单级，品牌是Parker/派克，型号是D31FW，适用范围是12，产品别名是21，材质是铁，适用介质是dd，适用温度是60（ ），公称压力是31（ MPa），公称通径是10（ mm），安装形式是falan，工作温度是常温，压力环境是高压