

梅特勒托利多SBS-1称重传感器

产品名称	梅特勒托利多SBS-1称重传感器
公司名称	上海兵杰电子科技有限公司
价格	1800.00/只
规格参数	品牌:梅特勒托利多 型号:SBS-1
公司地址	上海市金山区卫清西路421号六楼706室
联系电话	0550-4669782 13641637925

产品详情

sbs称重传感器、sbs悬臂梁传感器

产品简介introduction :

悬臂梁式；优质合金钢材质；高精度；高稳定性；通过ntep,cmc,oiml认证；安装简便、快速；表层镀镍防腐处理；适用于平台秤、搅拌站、皮带秤和配料秤

主要特点features: 悬臂梁式 优质合金钢材质 高精度 高稳定性 通过ntep,cmc,oiml认证 安装简便、快速 表层镀镍防腐处理 适用于平台秤、搅拌站、皮带秤和配料秤等

single ended shear beam load cell senior alloy steel high accuracy high stability
ntep, cmc, oiml approved easy to install protected against corrosion by nickelplated treatment
suitable for floor scales, blending & mixing systems, belt scales and batching systems, etc.

量程capacities: sbs-250lb, sbs-250kg, sbs-500kg, sbs-1000kg, sbs-1500kg, sbs-2000kg, sbs-2500kg,

sbs-5000kg, sbs-7500kg, sbs-10000kg 技术参数specification:

额定输出	rated output	3.0mv/v \pm 0.1%
零点平衡	zero balance	\pm 1% of rated output
蠕变	creep after 30 minutes	\pm 0.03% of rated output
非线性	nonlinearity	\pm 0.03% of rated output
滞后	hysteresis	\pm 0.03% of rated output

重复性	repeatability	± 0.03% of rated output
灵敏度温漂	temp. effect on output	0.002% of applied output/ ° c
零点温漂	temp. effect on zero	0.002% of rated output/ ° c
可用温度范围	safe temp. range	-10 ° c to + 70 ° c
温度补偿范围	temp. compensated	-10 ° c to + 40 ° c
安全载荷	safe overload	150%
输入阻抗	input impedance	387 ohm ± 20 ohm
输出阻抗	output impedance	350 ohm ± 5 ohm
绝缘阻抗	insulation resistance	5000 m ohm (50v dc)
推荐激励电压	rated excitation	10v dc/ac
最大激励电压	maximum excitation	15v dc/ac
导线长度	cable length	6m/1067cm
导线颜色	cable color code	red(+e) black(-e) green(+s) white(-s)