

Megger TDR 1000/3P 电缆故障定位仪 , 0-5000m

产品名称	Megger TDR 1000/3P 电缆故障定位仪 , 0-5000m
公司名称	天津固齐国际贸易有限公司
价格	面议
规格参数	加工定制:否 品牌:megger 型号:TDR1000/3P
公司地址	天津市西青区华苑产业区华科三路1号华鼎智地4-1204A
联系电话	86 022 58517110 13072262540

产品详情

megger tdr 1000/3p 电缆故障定位仪 , 0-5000m

技术参数分辨率 1 %型号 (p) tdr1000/3p宽度 48mm尺寸 115 x 48 x 230mm显示器类型 lcd最低工作温度 -15 ° c最大脉冲宽度 2ns最大范围 5000m最小脉冲宽度 4000ns最高工作温度 +50 ° c电池寿命 14 h电池类型 aa电源 电池电缆类型 金属电缆对脉冲幅度 5v pk-pk输出阻抗 100 , 25 , 50 , 75 速度因子/传播速度 0.99重量 0.6kg长度 115mm高度 230mm

megger tdr 1000/3p

the tdr1000/3p is a hand held, compact time domain reflectometer for locating faults on metallic cables. it has a minimum resolution of 0.1 m/0.3 ft and a 5 km/15 kft maximum range depending on velocity factor selected and cable type. four output impedances are available (25, 50, 75, and 100) and a velocity factor between 0.2 and 0.99 will meet any cable test requirements. the tdr1000 has a simple selection option which together with a 4 way control switch offers an intuitive operation for the user. an auto selection option ensures that the most effective parameters are selected depending on the range required, aiding rapid diagnosis of the tdr trace. dual cursors allow complete flexibility, giving the operator full control and instant indication of distance between two points. a trace hold feature also allows comparison between conditions, something not seen on most other handheld tdrs. extra high resolution together with white-light backlight and grey scale tones give the graphical display a vibrancy, aiding the user in identifying key events on the trace.the tdr1000/3p is supplied with a fused test lead set (764-2831) ready to test cat iv power circuits. a miniature clip test lead set to test telecom circuits is available separately (please see rs 764-2822)

dual cursors providing instant indication of distance between two pointsauto set up for instant useultra fast pulse for near end fault identificationtrace hold feature to allow comparison between cablesip54 rating offers real life workingdesigned for use on all metallic cable pairsbacklit graphics monochrome lcd (256 x 128)adjustable display contrastresolution to 0.1 mfor use on telecom tnv-3 circuit, or 150v cat iv power circuitspower blocking filter not requiredenvironmental protection to ip54auto selected output impedance (between 25, 50, 75 and 100)2 ns pulse

for near end fault locationauto option selecting gain and pulse for each rangedisplay distance in metres or feetuses five
aa (lr6) primary cells (supplied)

随附

5 x aa batteries, hard carry case, fused test lead set, user guide cd

本产品的加工定制是否，品牌是megger，型号是TDR1000/3P