

## 4-1440000-3 温度

产品名称	4-1440000-3 温度
公司名称	深圳市正欣达电子有限公司
价格	面议
规格参数	应用范围:温度 品牌:OEG/王利 型号:4-1440000-3
公司地址	深圳市南山区留仙洞大厦709
联系电话	13682663214

## 产品详情

**产品类型特性:**产品系列 = omi/omih端子类型 = pcb-tht  
**电气特点:**contact - current class = 5a to 10a class, less than 16a  
触点额定电流 (a) = 10  
contact - limiting continuous current (a) = 10  
contact - limiting making current (a) = 10  
contact - limiting breaking current (a) = 10  
insulation - initial dielectric between coil/contact class = >4000v  
class  
insulation - initial dielectric between open contacts (v rms) = 1000  
介电强度 - 线圈接触体 (v rms) = 5000  
contact - rated voltage (vac) = 250  
contact - switching voltage max. (vac) = 250  
contact - switching voltage max. (vdc) = 30  
contact - limiting short-time current (a) = 10  
contact - switching recommended load, min. = 100ma at 5v  
线圈电压 (vdc) = 24  
线圈电阻 (?) = 1100  
额定线圈功率 (mw) = 540  
coil - rated power class = 500mw to 600mw  
class  
insulation - initial insulation resistance (m?) = 1000000  
insulation - creepage class = 5.5mm to 8mm  
class  
insulation - clearance class = 5mm to 8mm  
class  
fcc 68 绝缘认证 = 10000v initial surge withstand voltage between contacts and coil  
尺寸:mechanical - length class = 25mm to 30mm  
class  
长度 (mm [in]) = 29.21 [1.150]  
mechanical - width class = 12mm to 16mm  
class  
宽度 (mm [in]) = 12.80 [0.504]  
mechanical - height class = 20mm to 25mm  
class  
高度 (mm [in]) = 20.60 [0.811]  
insulation - clearance between contact and coil (mm [in]) = 5.5 [0.217]  
insulation - creepage between contact and coil

**主体特性:**安装方式 = pcb  
重量 (g [oz]) = 13.00 [0.459]  
**触点特性:**contact material = agsno  
contact - number of poles = 1  
**配置特性:**触点组合形式 = 1 form c (co)  
线圈励磁系统 = monostable, dc  
coil - special features = ul coil insulation class a, sensitive  
**行业标准:**符合 rohs/elv 标准 = 符合 rohs 但不符合 elv 标准  
[符合 rohs 但不符合 elv 标准] 无铅焊接制程 = 波峰焊最高可达 260 ° c, 波峰焊最高可达 240 ° c, 波峰焊最高可达 265 ° c  
rohs/elv 符合记录 = 一直符合 rohs 而不是 elv approved/registered standards = cqc, ul, csa, vde  
**环境:**environmental - category of protection = rti  
environmental - ambient temperature, max. ( ° c [ ° f]) = 70 [158]  
environmental - ambient temperature class = 50 ° c to 70 ° c  
class  
**包装特性:**包装方式 = 盒装  
其他:品牌 = oeg

(mm [in]) = 8 [0.315]

本产品的应用范围是温度，品牌是OEG/王利，型号是4-1440000-3，产品系列是GMR，额定电流是24，额定电压是12