

高能点火放电管玻璃、陶瓷封装（汉孝）

产品名称	高能点火放电管玻璃、陶瓷封装（汉孝）
公司名称	孝感市汉孝电子有限公司
价格	面议
规格参数	品牌:汉孝 型号:R-12M 种类:真空式
公司地址	孝感市孝南经济开发区车站工业园区（长征路北段）
联系电话	2080176 13508638884

产品详情

汉孝电子公司高能点火放电管介绍

汉孝电子公司主要生产高能点火放电管，是生产高能点火放电管的专业厂家，r-12m、r50m型系列高能点火放电管，采用金属—玻璃、金属—陶瓷封接结构，具有重量轻、点火能级大，动态工作稳定，结构牢固，可在-45 —120 工作。直流击穿电压：2500 ± 5% v、2000 ± 5% v，能级水平：0~40 j，最大直径：28 mm，最大长度：43 mm，最大重量：34 g。同时我厂也可根据用户要求，提供直流击穿电压范围为500v-5000v的各种高能点火放电管。

主要性能参数对比表

类别	汉孝电子有限公司			
	r12m	r50m	r28m	r31m
型号 (type)	r12m	r50m	r28m	r31m
放电电压 (static breakdown voltage(100v/s)	2500v	2000v	2800v	3100v
击穿电压范围(tolerance(%))	± 5%	± 5%	± 5%	± 5%
绝缘电阻(100v)(isolation resistance)	10m	10m	10m	10m
最大放电能级	16j	16j	16j	16j

开户行：中国工商银行孝感市孝南区支行

帐号：1812021209200015397

税号：420902662268786

联系人：陈方斌

地址：孝感市长征路267号（安佑饲料厂内）

电话/传真：0712-2888230；13508638884

邮编：432100

e-mail：xgcfb@yahoo.com.cn

the hanxiao electron limited company

r-50m ,r-12m series of 2-electrode spark gas tube

description

the r-50m ,r-12m series of 2-electrode spark gas tubes are gas discharge tubes, hermetically sealed in a glass-metal envelope. tubes with a dc breakdown voltage in the range $2000v \pm 5\%$, $2500v \pm 5\%$ are available.

the spark gas tubes, matched with contacting cable and semiconductor spark plug can be widely used in high power ignitors which are fueled by natural gas, liquefied petroleum gas, diesel oil smog and heavy oil smog. after being cooperated with many companies, the products are proved to be of the characteristic of high spark power, compact, safe and reliable.

photo

electrical and physical characteristics

all rating given in this data sheet are absolute, non-simultaneous ratings. it is the equipment designer ' s responsibility to ensure that they are not exceeded. the spark gas tube ' s life depends on circuit conditions as peak discharge current and duration, charge transfer per discharge and the repetition rate.

outline(all dimensions in milimetres)

dc breakdown voltage rang $2000v \pm 20\%$

peak current, single discharge: 1800a

capacitance: 5pfmax

operating temperature: -55to+125

discharge frequency: 1hz

mechanical shock, half-sine: 40g for 4ms

energy level: 16j

insulation resistance in off state: 15m min

mounting: screw mounted

net weight: 35g max

max dais: 26mm

max length: 58mm

life: 3x10⁵

radioactivity: 137cs(0.5 μ ci max)

add:267 changzhend rd,xiaogan city,hubei province,china

tel/fax:0086-0712-2888230 , 13508638884 e-mail:xgcfb@yahoo.com.cn

本产品的品牌是汉孝，型号是R-12M，种类是真空式，额定电压是2500（V），额定电流是5000（A），接触电阻是0（ Ω ），绝缘电阻是100（M Ω ），产品性质是新品，营销方式是厂家直销，营销价格是优惠