## 二手 NEWPORT 8.25 平台

产品名称	二手 NEWPORT 8.25 平台	
公司名称	深圳市宇宙源光电科技有限公司	
价格	面议	
规格参数	样品或现货:现货 是否标准件:标准件 标准编号:8.25	
公司地址	深圳市南山区蛇口海昌街蓝虹豪苑8F*	
联系电话	13242083093 13715268029	

## 产品详情

	_
axes of travel	K
oad capacity	200 lb (900 n)
material	steel
pearings	ball
thread type	english
oad capacity,	100 n
centered with bm	
micrometer	
angular deviation	<200 µ rad
special features	double-row ball
	bearings
an a sigl factures of	auda wasu baasisas
special features: do	ouble row bearings
· low-profile des	ian stool
construction for h	_
rigidity - double-	•
for higher load cap	_
deviation better th	, ,
µ rad · threaded	
mounting	moromotor
Inodriding	
the umr8.25 precis	sion double-row ball
bearing linear stag	
construction for h	
	earings and precision-
ground bearing su	
	•

with utr and urm rotation stages, bgm goniometers, and sl series mirror mounts.	easily assembled using eq series angle brackets. umr stages are compatible	positioning. standard bm series micrometers provide 1 $\mu$ m sensitivity, while dm series differential micrometers offer 0.1 $\mu$ m. for coarse motion with position locking, a fixed positioning kit replaces the micrometer with two opposing adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer. motorized actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard. multi-axis stage configurations are easily assembled using eq series angle brackets. umr stages are compatible with utr and urm rotation stages, bgm goniometers, and sl series mirror	
easily assembled using eq series angle brackets. umr stages are compatible			
multi-axis stage configurations are easily assembled using eq series angle brackets. umr stages are compatible		easily stacked in an xy configuration	
easily stacked in an xy configuration and mounted to a table or breadboard. multi-axis stage configurations are easily assembled using eq series angle brackets. umr stages are compatible	easily stacked in an xy configuration and mounted to a table or breadboard.	component placement on the stage	
component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard. multi-axis stage configurations are easily assembled using eq series angle brackets. umr stages are compatible	component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard.	•	
patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard. multi-axis stage configurations are easily assembled using eq series angle brackets. umr stages are compatible	patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard.	actuators can be added for precision	
actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard. multi-axis stage configurations are easily assembled using eq series angle brackets. umr stages are compatible	actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard.		
opposite the micrometer. motorized actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard. multi-axis stage configurations are easily assembled using eq series angle brackets. umr stages are compatible	opposite the micrometer. motorized actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard.	,	
motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard. multi-axis stage configurations are easily assembled using eq series angle brackets. umr stages are compatible	screw that mounts in the stage body opposite the micrometer. motorized actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard.	•	
adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer. motorized actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard. multi-axis stage configurations are easily assembled using eq series angle brackets. umr stages are compatible	adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer. motorized actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard.		
micrometer with two opposing adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer. motorized actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard. multi-axis stage configurations are easily assembled using eq series angle brackets. umr stages are compatible	micrometer with two opposing adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer. motorized actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard.		
positioning kit replaces the micrometer with two opposing adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer. motorized actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard. multi-axis stage configurations are easily assembled using eq series angle brackets. umr stages are compatible	positioning kit replaces the micrometer with two opposing adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer. motorized actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard.	•	
motion with position locking, a fixed positioning kit replaces the micrometer with two opposing adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer. motorized actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard. multi-axis stage configurations are easily assembled using eq series angle brackets. umr stages are compatible	motion with position locking, a fixed positioning kit replaces the micrometer with two opposing adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer. motorized actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard.		
micrometers offer 0.1 µ m. for coarse motion with position locking, a fixed positioning kit replaces the micrometer with two opposing adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer. motorized actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard. multi-axis stage configurations are easily assembled using eq series angle brackets. umr stages are compatible	micrometers offer 0.1 µ m. for coarse motion with position locking, a fixed positioning kit replaces the micrometer with two opposing adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer. motorized actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard.		
while dm series differential micrometers offer 0.1 µ m. for coarse motion with position locking, a fixed positioning kit replaces the micrometer with two opposing adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer. motorized actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard. multi-axis stage configurations are easily assembled using eq series angle brackets. umr stages are compatible	while dm series differential micrometers offer 0.1 µ m. for coarse motion with position locking, a fixed positioning kit replaces the micrometer with two opposing adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer. motorized actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard.		
micrometers provide 1 \( \mu\) m sensitivity, while dm series differential micrometers offer 0.1 \( \mu\) m. for coarse motion with position locking, a fixed positioning kit replaces the micrometer with two opposing adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer. motorized actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard. multi-axis stage configurations are easily assembled using eq series angle brackets. umr stages are compatible	micrometers provide 1 µ m sensitivity, while dm series differential micrometers offer 0.1 µ m. for coarse motion with position locking, a fixed positioning kit replaces the micrometer with two opposing adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer. motorized actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard.		
micrometers offer 0.1 µ m. for coarse motion with position locking, a fixed positioning kit replaces the micrometer with two opposing adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer. motorized actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard. multi-axis stage configurations are easily assembled using eq series angle brackets. umr stages are compatible	positioning. standard bm series micrometers provide 1 µ m sensitivity, while dm series differential micrometers offer 0.1 µ m. for coarse motion with position locking, a fixed positioning kit replaces the micrometer with two opposing adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer. motorized actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard.	0.98 inch travel range. multiple drive	
options cover the range of precision positioning, standard bm series micrometers provide 1 \( \mu\) m sensitivity, while dm series differential micrometers offer 0.1 \( \mu\) m, for coarse motion with position locking, a fixed positioning kit replaces the micrometer with two opposing adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer, motorized actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface, two stages can be easily stacked in an xy configuration and mounted to a table or breadboard, multi-axis stage configurations are easily assembled using eq series angle brackets, umr stages are compatible	options cover the range of precision positioning, standard bm series micrometers provide 1 \( \mu \) m sensitivity, while dm series differential micrometers offer 0.1 \( \mu \) m. for coarse motion with position locking, a fixed positioning kit replaces the micrometer with two opposing adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer. motorized actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface, two stages can be easily stacked in an xy configuration and mounted to a table or breadboard.	smooth, backlash-free motion over a	
0.98 inch travel range. multiple drive options cover the range of precision positioning. standard bm series micrometers provide 1 µ m sensitivity, while dm series differential micrometers offer 0.1 µ m. for coarse motion with position locking, a fixed positioning kit replaces the micrometer with two opposing adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer. motorized actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard. multi-axis stage configurations are easily assembled using eq series angle brackets. umr stages are compatible	0.98 inch travel range. multiple drive options cover the range of precision positioning. standard bm series micrometers provide 1 μ m sensitivity, while dm series differential micrometers offer 0.1 μ m. for coarse motion with position locking, a fixed positioning kit replaces the micrometer with two opposing adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer. motorized actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard.		
constant micrometer contact for smooth, backlash-free motion over a 0.98 inch travel range. multiple drive options cover the range of precision positioning, standard bm series micrometers provide 1 \( \mu\) m sensitivity, while dm series differential micrometers offer 0.1 \( \mu\) m. for coarse motion with position locking, a fixed positioning kit replaces the micrometer with two opposing adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer, motorized actuators can be added for precision motion control, generous hole patterns allow great flexibility in component placement on the stage mounting surface, two stages can be easily stacked in an xy configuration and mounted to a table or breadboard. multi-axis stage configurations are easily assembled using eq series angle brackets, umr stages are compatible	constant micrometer contact for smooth, backlash-free motion over a 0.98 inch travel range. multiple drive options cover the range of precision positioning, standard bm series micrometers provide 1 \( \mu\) m sensitivity, while dm series differential micrometers offer 0.1 \( \mu\) m. for coarse motion with position locking, a fixed positioning kit replaces the micrometer with two opposing adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer, motorized actuators can be added for precision motion control, generous hole patterns allow great flexibility in component placement on the stage mounting surface, two stages can be easily stacked in an xy configuration and mounted to a table or breadboard.	5 5	
poreloaded by two springs to ensure constant micrometer contact for smooth, backlash-free motion over a 0.98 inch travel range. multiple drive options cover the range of precision positioning, standard bm series micrometers provide 1 \( \mu\) m sensitivity, while dm series differential micrometers offer 0.1 \( \mu\) m. for coarse motion with position locking, a fixed positioning kit replaces the micrometer with two opposing adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer. motorized actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface, two stages can be easily stacked in an xy configuration and mounted to a table or breadboard. multi-axis stage configurations are easily assembled using eq series angle brackets, umr stages are compatible	poreloaded by two springs to ensure constant micrometer contact for smooth, backlash-free motion over a 0.98 inch travel range. multiple drive options cover the range of precision positioning. standard bm series micrometers provide 1 \mu m sensitivity, while dm series differential micrometers offer 0.1 \mu m. for coarse motion with position locking, a fixed positioning kit replaces the micrometer with two opposing adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer. motorized actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface, two stages can be easily stacked in an xy configuration and mounted to a table or breadboard.		
202 lb. the moving carriage is preloaded by two springs to ensure constant micrometer contact for smooth, backlash-free motion over a 0.98 inch travel range. multiple drive options cover the range of precision positioning, standard bm series micrometers provide 1 \( \mu\) m sensitivity, while dm series differential micrometers offer 0.1 \( \mu\) m. for coarse motion with position locking, a fixed positioning kit replaces the micrometer with two opposing adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer, motorized actuators can be added for precision motion control, generous hole patterns allow great flexibility in component placement on the stage mounting surface, two stages can be easily stacked in an xy configuration and mounted to a table or breadboard, multi-axis stage configurations are easily assembled using eq series angle brackets, umr stages are compatible	202 lb. the moving carriage is preloaded by two springs to ensure constant micrometer contact for smooth, backlash-free motion over a 0.98 inch travel range. multiple drive options cover the range of precision positioning, standard bm series micrometers provide 1 µ m sensitivity, while dm series differential micrometers offer 0.1 µ m. for coarse motion with position locking, a fixed positioning kit replaces the micrometer with two opposing adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer. motorized actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard.	5	
choice for carrying high loads up to 202 lb. the moving carriage is preloaded by two springs to ensure constant micrometer contact for smooth, backlash-free motion over a 20.98 inch travel range. multiple drive options cover the range of precision positioning, standard bm series micrometers provide 1 \( \mu\) m sensitivity, while dm series differential micrometers offer 0.1 \( \mu\) m. for coarse motion with position locking, a fixed positioning kit replaces the micrometer with two opposing adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer, motorized pactuators can be added for precision motion control, generous hole patterns allow great flexibility in component placement on the stage mounting surface, two stages can be easily stacked in an xy configuration and mounted to a table or breadboard, multi-axis stage configurations are easily assembled using eq series angle brackets, umr stages are compatible	choice for carrying high loads up to 202 lb. the moving carriage is preloaded by two springs to ensure constant micrometer contact for smooth, backlash-free motion over a 20.98 inch travel range, multiple drive options cover the range of precision positioning, standard bm series micrometers provide 1 µ m sensitivity, while dm series differential micrometers offer 0.1 µ m, for coarse motion with position locking, a fixed positioning kit replaces the micrometer with two opposing adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer. motorized actuators can be added for precision motion control, generous hole patterns allow great flexibility in component placement on the stage mounting surface, two stages can be easily stacked in an xy configuration and mounted to a table or breadboard.	<u> </u>	
ball bearings making them an excellent choice for carrying high loads up to 202 lb. the moving carriage is perloaded by two springs to ensure constant micrometer contact for smooth, backlash-free motion over a 20.98 inch travel range, multiple drive options cover the range of precision positioning, standard bm series micrometers provide 1 \( \mu\) m sensitivity, while dm series differential micrometers offer 0.1 \( \mu\) m. for coarse motion with position locking, a fixed positioning kit replaces the micrometer with two opposing adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer, motorized actuators can be added for precision motion control, generous hole patterns allow great flexibility in component placement on the stage mounting surface, two stages can be easily stacked in an xy configuration and mounted to a table or breadboard, multi-axis stage configurations are easily assembled using eq series angle brackets, umr stages are compatible	ball bearings making them an excellent choice for carrying high loads up to 202 lb. the moving carriage is preloaded by two springs to ensure constant micrometer contact for smooth, backlash-free motion over a 20.98 inch travel range. multiple drive options cover the range of precision positioning, standard bm series micrometers provide 1 \( \mu\) m sensitivity, while dm series differential micrometers offer 0.1 \( \mu\) m. for coarse motion with position locking, a fixed positioning kit replaces the micrometer with two opposing adjustment screws and lock nuts. an optional carriage locking kit includes a screw that mounts in the stage body opposite the micrometer. motorized actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard.	•	
amr8 series stages have double-row pall bearings making them an excellent shoice for carrying high loads up to 202 lb. the moving carriage is preloaded by two springs to ensure constant micrometer contact for mooth, backlash-free motion over a 20.98 inch travel range, multiple drive options cover the range of precision positioning, standard bm series micrometers provide 1 µ m sensitivity, while dm series differential micrometers offer 0.1 µ m. for coarse motion with position locking, a fixed positioning kit replaces the micrometer with two opposing digustment screws and lock nuts. an optional carriage locking kit includes a crew that mounts in the stage body opposite the micrometer, motorized actuators can be added for precision motion control, generous hole catterns allow great flexibility in component placement on the stage mounting surface, two stages can be asily stacked in an xy configuration and mounted to a table or breadboard, multi-axis stage configurations are assily assembled using eq series angle prackets, umr stages are compatible	amr8 series stages have double-row ball bearings making them an excellent thoice for carrying high loads up to 202 lb. the moving carriage is preloaded by two springs to ensure constant micrometer contact for mooth, backlash-free motion over a 2.98 inch travel range. multiple drive options cover the range of precision positioning, standard bm series micrometers provide 1 µ m sensitivity, while dm series differential micrometers offer 0.1 µ m. for coarse motion with position locking, a fixed positioning kit replaces the micrometer with two opposing adjustment screws and lock nuts. an apptional carriage locking kit includes a crew that mounts in the stage body opposite the micrometer. motorized actuators can be added for precision motion control. generous hole patterns allow great flexibility in component placement on the stage mounting surface. two stages can be easily stacked in an xy configuration and mounted to a table or breadboard.	deviation better than 100-200 ju rad.	

本产品的样品或现货是现货,是否标准件是标准件,标准编号是8.25,品牌是NEWPORT,型号是8.25,材质是不锈钢,类别是多款供选,新旧程度是9成新,设备所在地是深圳,设备生产产地是法国,产品数量是2PCS