

耐高温贴片DC电源插座，全铜DC电源插座DC-091厂家直销DC插座

产品名称	耐高温贴片DC电源插座，全铜DC电源插座DC-091厂家直销DC插座
公司名称	东莞市韩晶电子有限公司
价格	面议
规格参数	加工定制:否 品牌:HJ 型号:DC-091
公司地址	东莞市桥头镇田新社区商业街60号
联系电话	13712896873 13751281893

产品详情

designation品名 : dc socket

model型号 :

edition版本 : 01

1.0构造tectonic

a型状、尺寸依照制品图而规定.shape, size in accordance with the provisions of map products.

b外观:各部位应良好无秤锈、裂痕、电镀不良现象.

appearance : the good parts should weigh no rust, cracks, electroplating ill.

2.0使用环境条件the use of environmental conditions

a环境湿度humidity:25 ~+70

b相对湿度relative humidity: 93% (+40)

c机械性能mechanical properties

d动作力power moves:3~25n

e端子强度terminal strength

各端子在各方面承受500克力作用下,在10秒内,无脱落、破损等不良现象,但弯曲也可.

the terminals in all aspects under 500caldon role, in 10 seconds, without any loss, damage and other negative phenomena

4.0电气性能electrical performance

a额定电流current ratings:dc 12v1a .

b接触电阻contact resistance:50m 以下.

c绝缘电阻insulation resistance:

在端子之间各端子与壳之间加ac 500v条件下,持续1分钟测试.100m 以上.the terminal between the terminal and shell conditions, sustained a minute test m above .100.

d抵抗电压resistance voltage:

在端子之间端子与壳之间加ac 500v 60hz条件下,持续1分钟测量.无击穿现象出现.in between the terminal and the to

60hz conditions, sustained a minute measurement. no breakdown phenomenon.

5.0可靠性试验reliability test

a寿命试验life test

以涂有薄层润滑脂的插头(涂润滑脂防止摩擦过热)以每分钟15~20次,无负载插座拔出5,000次 , 符合规格3.0和4.0
layer of grease plugs (tu grease prevent friction overheated) per minute to 15 ~ 20, a no-load socket allocated 5,000, with the specification required.

b温度试验temperature test

将插座放置于 40 ± 2 ,相对湿度90%~95%环境中,96个小时后取出,取去水滴,将插座放置于常温常湿环境中,于30分钟内测定,符合规格3.0和4.0要求.
socket to be placed on the 40 ± 2 , relative humidity of 90% ~ 95% of the environment, 96 hours after the removal, taking a drop of water, will be placed in the socket temperature often wet environment, in the test within 30 minutes, with 3.0 and 4.0 specifications required.

c耐热试验heat test

将插座放置于 70 ± 2 环境下,96个小时后取出,将插座放置于常温常湿环境中,于30分钟内测定,符合规格3.0和4.0要求.
socket to be placed on the 70 ± 2 environment, 96 hours after the removal of sockets placed on the temperature and moisture environment, within 30 minutes measured with 3.0 and 4.0 specifications required.

d耐寒试验hardy trial

将插座放置于 -40 ± 3 环境中,96个小时后取出,取去水滴,将插座放置于常温湿环境中.于30分钟内测定,符合规格3.0和4.0要求.
socket to be placed on the -40 ± 3 environment, 96 hours after the removal, taking a drop of water, will be placed in the socket temperature often wet environment. within 30 minutes measured with 3.0 and 4.0 specifications required.

5.5耐焊接热试验thermal resistance welding test

插座耐焊接热试验中,符合规格3.0和平共处4.0要求.

socket welding thermal resistance test, with the specifications required 4.0 3.0 peaceful coexistence.

a自动焊;温度 235 ± 5 ,时间 5 ± 1 秒.automatic welding; temperature of 235 ± 5 , ± a time five seconds.

b人动焊;温度 350 ± 10 ,时间 3 ± 0.5 秒.people to welding; the temperature of 350 ± 10 for 3 ± 0.5 seconds.

本产品的加工定制是否 , 品牌是HJ , 型号是DC-091 , 额定电流是1 (A) , 额定电压是12 (V) , 环境温度是耐高温260度 () , 壳体材质是尼龙 , PBT,LCP,ABS , 导电体材质是磷铜 , 猛钢 , 产品认证是ROHS,REACH