

新品！超微 supermicro SuperServer 6027AX-TRF

产品名称	新品！超微 supermicro SuperServer 6027AX-TRF
公司名称	深圳市星宏伟业科技有限公司
价格	面议
规格参数	品牌:超微supermicro 型号:6027AX-TRF 支持CPU: Intel Xeon processor E5-2600
公司地址	深圳市福田区梅华路105号多丽工业区科技楼604
联系电话	0755-83005001

产品详情

superserver 6027ax-trf

主要特点：

- cooling optimized solution • support hyper-speed

1. intel® xeon® processor e5-2600 family; qpi up to 8gt/s

2. up to 512gb ddr3 1600mhz ecc registered dimm; 16x dimm sockets

3. 2x pci-e 3.0 x16, 3x pci-e 3.0 x8, 1x uio pci-e 3.0 x8 (for smc uio) or 1x pci-e 2.0 x4 (in x8)

4. i/o ports: 2 gbe lan, 4 usb 3.0, 2 hd/ac97, 1 ipmi dedicated lan ports, and 2 ieee 1394 header

5. 10x hot-swap 3.5" hdd bays

6. 1280w redundant power supplies 80 plus, platinum level (95%)

product skus		
sys-6027ax-trf	superserver 6027ax-trf (black)	
motherboard		
super x9dax-if		
processor/cache		
cpu	intel® xeon® processor e5-2600 (up to 150w tdp) dual socket r (lga 2011)	
cache	up to 20mb	
system bus	qpi up to 8 gt/s	
system memory		
memory capacity	16x 240-pin ddr3 dimm sockets supports up to 512 gb ddr3 ecc registered memory (rdimm) supports up to 128 gb ddr3 ecc un-buffered memory (udimm)	
memory type	1600/1333/1066/800mhz ecc ddr3 sdram 72-bit, 240-pin gold-plated dimms	
dimms sizes	32gb, 16gb, 8gb, 4gb, 2gb, 1gb	
memory voltage	1.5 v, 1.35 v	
error detection	corrects single-bit errors detects double-bit errors (using ecc memory)	
on-board devices		
chipset	intel® c602 chipset	
sata	sata 2.0 3gbps with raid 0, 1, 5, 10 sata 3.0 6gbps with raid 0, 1	
ipmi	support for intelligent platform management interface v.2.0 ipmi 2.0 with virtual media over lan and kvm-over-lan support nvidia wpcm450 bmc	
network controllers	intel® i350 dual port gigabit ethernet virtual machine device queues reduce i/o overheads supports 10base-t,	

chassis	
form factor	2u rackmount
model	cse-829btq-r1k28lpb
dimensions	
width	17.2" (437mm)
height	3.5" (89mm)
depth	25.5" (648mm)
gross weight	52 lbs (23.6kg)
available colors	black
front panel	
buttons	power on/off buttons system
leds	power status led hard drive activity leds system over
expansion slots	
pci-express	2 pci-e 3.0 x16 slots 3 pci-e x8 (for smc uio) or 1 pci-e
drive bays	
hot-swap	10x hot-swap 3.5" sata hdd
display	
lcd screen	front panel lcd display (10.4")
backplane	
1x sas2 / sata backplane	
system cooling	

	100base-tx, and 1000base-t, rj45 output rtl8201n phy (dedicated ipmi)	output 1x realtek			
audio	realtek alc889 7.1 high definition header	audio with s/pdif			fans 4x pwm fans w/ optimal
graphics				matrox g200e	heatsink optional 2x passive cpu
input / output					power supply 1280w redundant high-efficiency digital po
serial ata	2x sata 3.0 ports (6gbps) 8x sata 2.0 ports (3gbps)				ac input 1000w output @ 100-14 output @ 180-240v, 8-6
lan	2x rj45 gigabit ethernet lan ports lan port	1x rj45 dedicated ipmi			dc output 1000w: +12v/83a; +5vsb +5vsb/4a
usb	4x usb 3.0 (2 front, 2 rear) and 4x usb 2.0 ports				certification 80 plus platinum [test r
audio	line-in / line-out / microphone ports				system bios
video	1x vga port				bios type 128mb spi flash eeprom
serial port / header	2x fast uart 16550 ports				bios features plug and play (pnp) apm keyboard support smbic
					operating environment / compliance
					rohs rohs compliant
					environmental spec. operating temperature: to 95 ° f) non-operating 70 ° c (-40 ° f to 158 ° f) humidity: 8% to 90% (no operating relative humidit condensing)

see parts list				
parts list - (items included)				
	part number	qty	description	
motherboard / chassis	mbd-x9dax-if	1	super x9dax-if motherboard	
	cse-829btq-r1k28lpb	1	2u chassis	
backplane	bpn-sas-829btq	1	10 hdd bpn, sgpio only support; added precharged r swap	
cable 1	cbl-0157l	2	8pin to 8pin ribbon cable with tube for sgpio, 40cm,	
cable 2	cbl-0157l-01	1	8pin to 8pin cable for sgpio, 61.5cm, pbf	
cable 3	cbl-0481l	2	81cm sata 30 awg flat s-s hf	
cable 4	cbl-0483l	3	29cm 30awg sata cable	
cable 5	cbl-0484l	5	55cm 30awg sata-sata s-s cable	
power supply	pws-1k28p-sq	2	1u 1280w, redundant single output power supply	
optional parts list				

	part number		qty	description
heatsink / retention	snk-p2048p		-	2u passive cpu heat sink for x9 over-clocking series s

本产品的品牌是超微supermicro，型号是6027AX-TRF，支持CPU是IntelXeonprocessorE5-2600，支持内存容量是512GB