

a48y-16c	20	15	105	75		55	16	2		4-14	25	115	85		65	16	2		4-14	110	95	411
a44y-16c	25	16	115	85		65	16	2		4-14	32	140	100		78	18	2		4-18	110	95	411
a44y-16p	32	20	140	100		78	18	2		4-18	40	150	110		85	18	3		4-18	115	100	411
a44y-16r	40	25	150	110		85	18	3		4-18	50	165	125		100	20	3		4-18	120	110	472
	50	32	165	125		100	20	3		4-18	65	185	145		120	20	3		4-18	135	120	532
	65	40	185	145		120	20	3		4-18	80	200	160		135	20	3		8-18	160	140	556
	80	50	200	160		135	20	3		8-18	100	220	180		155	22	3		8-18	170	135	561
	100	65	220	180		155	20	3		8-18	125	250	210		185	22	3		8-18	195	175	667
	125	80	250	210		185	22	3		8-18	150	285	240		210	24	3		8-23	210	190	857
	150	100	285	240		210	24	3		8-23	175	310	270		240	26	3		8-23	255	230	915
	200	125	340	295		265	26	3		12-23	250	405	355		320	30	3		12-26	300	260	1073
	250	150	405	355		320	30	3		12-26	300	460	410		375	30	4		12-26	350	320	1307
	300	220	460	410		375	30	4		12-26	400	580	525		485	36	4		16-30	370	350	1233
	350	250	520	470		435	34	4		16-26	500	715	650		608	44	4		20-34	500	450	1711
	400	280	580	525		485	36	4		16-30	500	715	650		608	44	4		20-34	500	450	1780

本产品的加工定制是是，品牌是永一，型号是A48Y，连接形式是法兰，材质是不锈钢，阀瓣开启高度是全启式安全阀，结构形式是弹簧式，公称通径是15-500（mm），适用介质是蒸汽，标准是美标，流动方向是单向，零部件及配件是阀体，压力环境是高压，类型(通道位置)是直角式，阀体构造是不封闭式，规格是15-500mm