

	b2mm														
	c1mm	160	160	188	188	188	240	240	240	290	290	380	380	380	410
	c2														
	db	5"	5"	6"	6"	6"	8"	8"	8"	10"	10"	10"	12"	12"	14"
	emm	60	60	80	80	80	80	80	80	100	100	100	100	100	200
	fmm	60	60	80	80	80	60	60	80	80	80	80	80	80	80
管径	冷媒入口cu	5/8"	5/8"	7/8"	1"	1-1/8"	1-1/8"	1-1/8"	1-3/8"	1-5/8"	2-1/8"	2-1/8"	2-1/8"	3"	3"
	冷媒入口cu	1-2"	5/8"	5/8"	3/4"	7/8"	7/8"	7/8"	1-1/8"	1-1/8"	1-5/8"	1-5/8"	1-5/8"	1-5/8"	1-5/8"
	可熔栓											1/4"			
	冷却水口b	1"	1"	1-1/2"	1-1/2"	1-1/2"	2"	2"	2-1/2"	3"	3"	3"	4"	4"	4"
筒身厚	mm	4	4	4	4	4	5	5	5	5	5	5	6	6	6
管板厚	mm	25	25	25	25	25	25	25	25	25	25	25	28	28	28
铜管直径	cu	1/2"	5/8"	5/8"	5/8"							5/8"			
散热面积	m ²	1.49	2.48	3.96	4.95	5.95	7.43	9.98	14.98	20.01	24.98	29.95	40.01	50.05	59.41
水量	m ³ \\h	1.58	2.15	4.00	4.8	9.38	12.5	18.75	25.0	15.63	28.13	31.25	37.5	37.5	50
重量	kg	16	28	47	53	53	88	105	140	88	175	158	210	210	280

本产品的加工定制是是，类型是油冷却器，品牌是广凌昌，型号是WSL-50，功率是30（KW），重量是80（kg），用途是工业冷却，水冷却等，结构形式是卧式，型号种类是GL系