

非隔离工控电源 高频高压工控电源

产品名称	非隔离工控电源 高频高压工控电源
公司名称	深圳市鑫通泰科技有限公司
价格	面议
规格参数	品牌:新巨 型号:M1P1-5500V4H 类型:高压电源
公司地址	深圳市福田区福华路鸿图大厦302室
联系电话	15018519890 13926502679

产品详情

温馨提示：

图片和价格仅供参考，如有需要请联系卖家，擅自下单者我们有权不进行发货

dimension...

250x84x41.8(mm) 9.84x3.31x1.65(inch)

ac input spec...

voltage : 90 ~ 264vac full range frequency : 47 ~ 63hz input current : 4a (rms) for 230vac 8a (rms) for 115vac inrush current : 40a max. for 115 vac per module 60a max. for 230 vac per module

dc output spec...

output voltage	output current min.	output current max	regulation load	regulation line	output ripple & noise max.[p-p]
+5v	0.5	32	± 5%	± 1%	50mv
+12v	2	41	± 5%	± 1%	120mv
-12v	0.1	0.5	± 5%	± 1%	120mv
+3.3v	0.5	25	± 5%	± 1%	50mv
+5vsb	0.1	3.5	± 5%	± 1%	50mv

* the output power of +5v and +3.3v not exceed 170w

features...

* temperature range : operating 0 ~ 40 , storage -20 ~ 80 * hold up time : when power shutdown dc output 5v must be maintain 16msec in regulation limit at normal input voltage.
 * dielectric withstand : input/output 1500 vac for 1 minute, input to frame ground 1500 vac for 1 minute* efficiency : typical >80% at 230v, full load* power good signal : on delay 100ms to 500ms , off delay 1ms* over power protection : 110 ~ 160% max* over voltage protection : +12v 13.2v~15.6v, +5v 5.7v~6.5v, +3.3v 3.9v~4.7v* over current protection: the power supply shall latch off if the +5v, +12v, +3.3v output currents are over it ' s limitation. the limited current is over 110~160% for each power module* short circuit protection: +5v, +12v, -12v, +3.3v* remote on/off control* safety : to meet ul, cul, tuv, ccc*the power-supply is for chassis-assembly only and is not allowed to be operated as stand-alone component. final assembly has to comply with corresponding emc- and safety-regulations.

本产品的品牌是新巨，型号是M1P1-5500V4H，类型是高压电源，调制方式是脉冲宽度调制(PWM)式，晶体管连接方式是推挽式，输入电压是115（V），输出功率是117（W），输出电压是12（V），工作效率是75（%），输出纹波噪音是低于100mv，输出电压精度是90（%），电压调整率是0.5（%），负载调整率是10（%），产品认证是CCC，输出电流是10A