

正宗台湾明纬电源开关S-50-24

产品名称	正宗台湾明纬电源开关S-50-24
公司名称	温州市民通电气有限公司
价格	面议
规格参数	品牌:MeanWell/明纬 型号:正宗台湾明纬电源开关S-50-24 类型:电台电源
公司地址	中国 浙江 乐清市 黄华工业区
联系电话	86 0577 61732969

产品详情

明纬开关电源 现货大量销售s-15-5s-15-12s-15-24s-25-5s-25-12s-25-15s-25-24s-35-5s-35-12s-35-15s-35-24s-40-5s-40-12s-40-15s-40-24s-50-5s-50-12s-50-15s-50-24s-60-5s-60-12s-60-15s-60-24s-100-3s-100-5s-100-7.5s-100-10s-100-12s-100-15s-100-24s-100-27s-100-48s-100-18s-100f-7.5s-100f-12s-100f-15s-100f-24s-100f-48s-100f-5s-150-5s-150-7.5s-150-9s-150-12s-150-15s-150-24s-150-48s-150-13.5s-150-27s-240-5s-240-7.5s-240-12s-240-15s-240-24s-240-30s-240-48s-320-5s-320-7.5s-320-12s-320-13.5s-320-15s-320-24s-320-27s-320-48sp-500-12sp-500-13.5sp-500-15sp-500-24sp-500-27sp-500-48d-30ad-30bid-30bd-50bd-60ad-60bid-60bd-120ad-120bid-50aid-50bid-50cid-50dd-50at-30bt-30at-40at-40bt-40ct-50at-50bt-50ct-50dt-60at-60bt-60cit-60fit-60dq-60bq-60cq-60diq-60diq-60fq-120bq-120cq-120dsp-75-3.3sp-75-5sp-75-7.5sp-75-12sp-75-13.5sp-75-15sp-75-24sp-75-27sp-75-48sp-100-3.3sp-100-5sp-100-7.5sp-100-12sp-100-13.5sp-100-15sp-100-24sp-100-27sp-100-48sp-150-3.3sp-150-5sp-150-7.5sp-150-12sp-150-13.5sp-150-15sp-150-24sp-150-27sp-150-48sp-200-3.3sp-200-5sp-200-7.5sp-200-12sp-200-13.5sp-200-15sp-200-24sp-200-27sp-200-48s-201-7.5s-201-12s-201-13.5s-201-15s-201-24s-201-27s-201-48s-201-5s-350-7.5s-350-12s-350-13.5s-350-15s-350-24s-350-27s-350-48s-350-5s-250-5s-250-12s-250-15s-250-24s-250-27s-250-48se-600-5se-600-12se-600-15se-600-24se-600-27se-600-48sp-320-5sp-320-7.5sp-320-12sp-320-13.5sp-320-15sp-320-24sp-320-27sp-320-48usp-350-15usp-225-3.3usp-225-5usp-225-12usp-225-15usp-225-24usp-225-48drp-480-24drp-480-48sp-480-3.3sp-480-5sp-480-12sp-480-15sp-480-24sp-480-48s-145-5s-145-7.5s-145-12s-145-15s-145-24s-210-5s-210-7.5s-210-12s-210-13.5s-210-15s-210-24s-210-27s-210-48se-1000-5se-1000-9se-1000-12se-1000-15se-1000-24se-1000-48rps-60-3.3rps-60-5rps-60-12rps-60-15rps-60-24rps-60-48rpd-60arpd-60brpt-60arpt-60brpt-60crpt-60drpt-6003

本产品的品牌是MeanWell/明纬，型号是正宗台湾明纬电源开关S-50-24，类型是电台电源，调制方式是脉冲宽度调制(PWM)式，晶体管连接方式是推挽式，输入电压是220380110 (V)，输出功率是15~1500 (W)，输出电压是220 (V)，工作效率是30 (%)，输出纹波噪音是20，输出电压精度是5 (%)，电压调整率是3 (%)，负载调整率是3 (%)，产品认证是CCC