



15	zx37-11	23	11	2.2	2.2	2.2	2.2	2.2	zh-2-6	
16	zx37-16	19	16	3.2	3.2	3.2	3.2	3.2	zh-2-7	
17	zx37-2	53	2	0.4	0.4	0.4	0.4	0.4	zh-3-1	
18	zx37-2.5	47	2.5	0.5	0.5	0.5	0.5	0.5	zh-3-2	20
19	zx37-3.3	41	3.3	0.66	0.66	0.66	0.66	0.66	zh-3-3	
20	zx37-4	37	4	0.8	0.8	0.8	0.8	0.8	zh-3-4	
21	zx37-5	34	5	1	1	1	1	1	zh-3-5	
22	zx37-6.6	29	6.6	1.32	1.32	1.32	1.32	1.32	zh-3-6	
23	zx37-7	28	7	1.4	1.4	1.4	1.4	1.4	zh-3-7	
24	zx37-9	25	9	1.8	1.8	1.8	1.8	1.8	zh-3-8	
25	zx37-11	23	11	2.2	2.2	2.2	2.2	2.2	zh-3-9	
26	zx37-14.5	20	14.5	2.9	2.9	2.9	2.9	2.9	zh-3-10	
27	zx37-19.5	17	19.5	3.9	3.9	3.9	3.9	3.9	zh-3-11	
28	zx37-28	14	28	5.6	5.6	5.6	5.6	5.6	zh-3-12	
29	zx37-35	13	35	7	7	7	7	7	zh-3-13	
30	zx37-44	11	44	8.8	8.8	8.8	8.8	8.8	zh-3-14	
31	zx37-58	9.8	58	11.6	11.6	11.6	11.6	11.6	zh-3-15	
32	zx37-80	8.4	80	16	16	16	16	16	zh-3-16	

#### 技术性能参数

zx37系列电阻器安全可靠，具有耐腐蚀、无感应电阻值稳定（误差为7.5%）。使用寿命长等优点，电阻器的功率可达5.6kw，适用于各类绕线型号的电动机的配套组合。

#### 外形及安装尺寸

本产品的品牌是永上YONSA，型号是ZX37-80，种类是排阻，性能是特殊，材料是金属膜，制作工艺是普通线绕，外形是管形，温度系数是PTC，产品性质是热销，营销方式是厂家直销