金桥机械供应棉纺包芯纱络筒机

产品名称	金桥机械供应棉纺包芯纱络筒机
公司名称	张家港市金桥轻工机械有限公司
价格	面议
规格参数	加工定制:是 种类:络筒机 型号:JQL5325
公司地址	张家港市塘桥镇青龙村上相
联系电话	58435120 13962292688

产品详情

该络筒机是专为大圆机厂及棉纺织厂、毛纺织厂，在细纱机上加工氨纶品种除外的各种包芯纱而特别设计制造的，解决了生产包芯纱过程中纱线张力问题。每锭三只筒管同时饶线，使其生产效率、产量、成型、松紧度和最终产品质量达到所有客户要求。文字介绍↓

该络筒机是专为大圆织机厂以及棉纺织厂、毛纺织厂，在细纱机上加工，氨纶品种除外各种包芯纱丝而特别设计制造的，解决了生产包芯纱过程中纱线张力问题，每锭三只管筒同时卷绕，使其生产效率、产量、成型、松紧度和最终产品质量达到所有客户要求。

this cone winding machine is designed for great circle toom factory and textife factory, woolen mill. it is specially designed for various kinds of core-spun yarn except spandex to processed on the spinning frame.lt

solved the thread tension problem during the producing of core-spun yarn,jhree winding drums per spindle to wind up to improve production efficiency,output,shaping,tension and quafity of final products to meet all customer needs.

技

术

参

数

（technical parameter）

↓

技术参数（technical parameter）	
名称 machine type	jql5325
控制方式control mode	衡线速控制 value-wire-speed control
生产速度production speed	600米／分 600 m／min
起动速度start-up speed	1-300秒可调 1-300 seconds is adjustable
定长设置fixed-length settings	100-990000米可调 100-990000 meters is adjustabt
驱动方式driven mode	每锭、二台交流电机、一台专用变频器 every spindle, two sets of ac motor, one special inve
张力调整tension adjustment	每锭配：可调式张力器 allocation of each spindle: djustable tension device
卷绕筒管winding bobbin	85mm*58mm
卷绕直径winding diameter	250mm*45mm
每节锭数the number of each ingot	5锭(每锭三只筒管 5spindles(3 bobbins/spindle
供电电压supply voltage	三相220v 50-60hz three-phass 220v 50-60h.z
安装尺寸 installed-size	1990mm(长)*700mm (宽)*1400 (高) 1990mm(length) * 700mm (width) * 1400 (h)
适应品种adapt varieties	锦纶、涤纶、涤丙复合丝. （粘胶丝）, pbt. nylon, polyester, polyester /propylene compound

本产品的加工定制是是，种类是络筒机，型号是JQL5325，品牌是JQ，规格是包芯纱