

纯环保白胶 强力荷 606

产品名称	纯环保白胶 强力荷 606
公司名称	武汉强力荷新材料有限公司
价格	面议
规格参数	品牌:强力荷 型号:606 粘合材料:纸塑/纸-板
公司地址	中国 湖北 武汉市 湖北省武汉市湖北大学化工大楼D322
联系电话	86 027 13971517886/13212744592 13297037817

产品详情

hu-606水性环保型纸塑/木包边胶

使用说明书

一、性能简介：

本品为水基型高分子聚合物乳胶，不含有机溶剂，无毒，不污染环境，固含量高，粘接速度快，广泛用于高档糖、酒、茶叶、月饼等硬挺型木质或纤维板内衬板与外装饰用覆膜纸的裱糊与包边粘合，粘接的包装盒无异味，符合绿色环保及食品卫生要求。

二、技术指标：

1. 外观：白色粘稠乳液；
2. 气味：无异味或略带清淡酯香味；
3. 粘接强度： 3.8n/25mm或纸拉破；
4. 固含量： 38%；
5. 贮存期： 1年。

三、用法与用量

将本品涂于覆膜纸的纸面上，涂胶量适当大一些为好，涂胶后将木盒或纤维板盒放在涂胶纸面上，逐步将盒子包装于面纸内，在2—6分钟（视室内温度、湿度和涂胶量的大小而变）观察到胶层部分透明时折边、搭口，用力压合。面纸上沾污的干胶可用酒精擦掉（湿的用湿抹布）。包装盒粘接后24小时达到最大粘接强度。

四、包装、运输与贮存：

本品用50kg聚乙烯塑料桶包装，按非危险物品运输与贮存，贮存于阴凉处。

hu - 606 water-based environmental protection packaging adhesive

product instruction booklet

一、introduction to functions

this product is a water-based polymer emulsion, which does not contain organic solvent, non-toxic, and no pollution. this product has many advantages including high solid content and bonding speed. it is widely used in are widely used in pasting paper on and package edge bonding the stiff grey board or wood fiber board and outside decoration color coated paper such as high-grade sugar, wine, tea, and cakes. there are no peculiar smell in adhesive packing box, in line with the green environmental protection and food hygiene requirements. this product conforms to the green environmental protection and food hygiene requirements.

二、technical indicator

1. appearance : white viscous emulsion
2. odour : no odor or slightly light ester fragrance
3. bonding strength : 3.8 n/p 25 mm or paper break down
4. solid content : 48% or more
5. the total volatile organic compounds : 0.05% or less
6. benzene and dimethyl benzene content % : 0.001 or less
7. storage period : 1 or more

三、method of application

- 1.put this product in plastic machine plastic plate, adjust the glueamount according to the paper thickness of hardness
- 2.wrapping paper placed 2-3 minutes show viscous after laminating. then it can be used on the bag pressing machine to stamping or use the scraper to scrape the packing box together.

四、matters needing attention

- 1.please use small mixer to mix glue in barrels before employ.

2. please cover the lid after using the glue to prevent the gel.

3. pay attention to preservation the glue barrel heat in winter.

4. it is the optimal time that a half dry wet 70% transparent to adhesion after the paper laminating, workers can judge and grasp the optimal timing of adhesive by experience (it is easy to bounce off with fail to stick if bottom of the bag, there are no adhesive after glue layer solidification too late).

5. due to water environmental protection glue affected by the workshop, such as temperature, humidity, and paper, it is dried quickly in summer and slowly in winter, pay attention to adjust the optimal timing of glue.

本产品的品牌是强力荷，型号是606，粘合材料是纸塑/纸-板