

LYMFB-I 防爆胶泥/密封胶泥/防爆电气/专用胶泥LYMFB-1

产品名称	LYMFB-I 防爆胶泥/密封胶泥/防爆电气/专用胶泥LYMFB-1
公司名称	浙江隆迈防爆电气有限公司
价格	10.00/公斤
规格参数	加工定制:是 品牌:lmfb 材质:高分子聚合物
公司地址	浙江省温州市乐清市柳市镇金丝河村(注册地址)
联系电话	18367862323

产品详情

适用范围:爆炸性气体混合物危险场所;1区 2区.爆炸性气体混合物 iia iib iic application。hazardous location;division 1&2。explosive gas atmospheres;iia iib iic 主要性能指标1.耐热度;90 ,5小时不流淌,不起泡2.耐低温;-50 不变化3.可塑性;5~10(mm)4.气密性;管 50mm,填充高度50mm穿入四根固定的电线0.5kg/cm³的气压,15分钟不产生气泡5.防爆性;32.2%混合氢气传爆试验,不传爆6.击穿电压;2.5mm厚的试件耐压1分钟,试验电压 > 10kv main performance index1.high temperature resistance;90 ,with neither flow nor bubbles within 5 hours2.low temperature resistance;-50 without change3.plasticity;5~10(mm)4.airtightness;tube filling height 50mm,thread in four fixed wires,0.5kg/cm³ air pressure no bubbles will occur within 15 minutes5.explosion-proofness;incendive test for 32.2%hydrogen mixture;not incendive6.punch through voltage;2.5mm thick sample can resist the voltage for one minute test voltage > 10kv

产品特点采用高分子聚合物,填加剂和稳定剂等配制而成,是一种无规则外形的胶泥状物,广泛应用于国防石油化工及其他方面的爆炸危险场所,作为钢管或电缆配线工程的防爆隔离密封材料,是科研生产中防爆隔离密封手段的选择,产品已获得防爆检验合格证书具有良好的柔软性能,长年保持不变,附着能力强气密性好不传爆.该材料无味 无毒 无腐蚀性 施工方便 features compounded with macromolecule polymer additive stabilizer and etc it is a kind of cementing substance with irregular shapes widely used in the explosion hazardous sites in national defence petroleum chemicals and other fields as the explosion-proof insulating and sealing materials in the steel tubes/cables wiring engineering it is the optimal choice for the explosion-proof isolating sealing means in the scientific research and production the product has been awarded the explosion-proof inspection qualification certificate It possesses high-quality soft performance and can be maintained for long years It's strongly adhesive and well airtight without the possibilities of being incendive the material is smellless innocuous non-corrosive and convenient for construction 粉剂密封填料以矿物质石膏为主要原料,以无机盐类有机化合物高分子化合物为配料,经混合搅拌而成,以粉剂密封填料与防爆隔密封盒配合使用,可达到防爆隔离密

封的作用 sealed packing of powder is made up through the mixture with mineral gypsum as main raw materials and inorganic salt-class organic compounds and macromolecule polymers as supplementary materials the powder sealing filler can be used in match with explosion-proof isolating and sealing box realizing the function of explosion-proof insulation and sealing 产品特点具有较好的抗压强度和凝固力，有一定的气密性和耐腐蚀能力，充填在防爆隔离密封盒内，不传爆，便于填充维修，现场施工方便等特点 features It possesses comparably good anti-compression strength and wrap-grip strength as well as airtightness and corrosion resistance capacity to some extents the filling process is conducted within the explosion-proof isolating and sealing boxes and has the characteristics such as; not incendiary convenient for filling and maintenance and easy for field construction etc 主要性能指标 1. 外观；灰白色粉末 2. 凝固时间；40 ~ 60 分钟 3. 抗压强度；不小于 100kg/cm² 4. 凝固力；不小于 150kg/cm² 5. 胶泥包装 1 箱；20kg 25kg 1. appearance; hoar powder 2. concreting time; 40 ~ 60 minutes 3. anti-compression strength; no less than 100kg/cm² 4. wrap-grip strength; no less than 150kg/cm² 5. one cementing package box; 20kg 25kg

qq 434618839 13388559070

本产品的加工定制是是，品牌是新黎明龙云飞策燎原腾达，材质是高分子聚合物，型号是LYMFB-IMF-IMFB-I，尺寸是无规则外形，重量是随意，适用范围是气体混合物危险场所;1区2区