

柔性凸版印刷机 层叠式 双色

产品名称	柔性凸版印刷机 层叠式 双色
公司名称	瑞安市瑞泰印刷包装机械有限公司
价格	面议
规格参数	加工定制:是 柔印机类型:层叠式 印刷颜色:双色
公司地址	中国 浙江 温州 瑞安市 上望街道永光工业区
联系电话	86 0577 65135631 15867716023

产品详情

yt 型系列二色柔性凸版印刷机

two color flexography bag printing mac hine

用途:

该机适合印刷聚乙烯、聚丙烯塑料袋、玻璃纸、卷筒纸,无纺布等包装材料,是食品包装,超市手提袋、马夹袋、服装袋,无纺布袋等包装的理想印刷设备。

性能和特点:

- 1、操作简便,起动柔和,套色准确。
- 2、计米器可根据要求设定印刷数量,到数自动停机,断料自动停机。
- 3、手动起落印版滚筒,升降后油墨自动搅拌。
- 4、网纹滚筒传墨,墨色均匀。
- 5、可靠的干燥系统,配合高速运转,停机自动断路。

6、360度连续可调的纵向对花装置。

7、进口变频电机调速，适应不同印刷速度。

8、版辊座上及收料架上均装有点动及停止按钮，便于装版时操纵机器

use:this machine is suitable for printing such packing materials as polyethylene,polypropylene plastic bag,cellophane and roll paper,etc.and it is a kind of ideal printing equipment for producing paper packing bag for food ,supermarket carry bag ,vest bag and clothes bag,etc.

characteristics:1.easy operation,flexible starting,accurate colour register.

2.the meter counter can set printing quantity according to the requirements.stop the machine automatically at the set quantity or when the material is cut off.

3.lift and lower the printing plate cylinder manually,it will automatically stir the printing ink after lifting.

4. the printing ink is spread by the knurled cylinder with even ink colour.

5.reliable drying system coordinated with high-speed rotation,it will automatically break circuit it when the machine stops.

6.360 continuous and adjustable register device.

7.the imported frequency control of motor speed adapts to different printing speeds,

8.there are inching/stopping buttons on the plate roller base and material rolling rack so as to make it easy operate the machine when the plate is installed.

主要技术参数

model	yt-2600	yt-2800	yt-21000
基材宽度	600mm	800mm	1000mm
最大印刷宽度	560mm	760mm	960mm
印刷长度	228 -914mm	228 -914mm	228 -914mm
最大直径	450mm	450mm	450mm
印刷速度	5 -50m /min	5 -50 m /min	5 -50 m /min
厚度	2.38mm	2.38mm	2.38mm
功率	8kw	10kw	12kw
总重量	1800kg	2000kg	2200kg
外形尺寸 (mm)	2300 × 1860 × 2145	2300 × 2060 × 2145	2300 × 2260 × 2145

main technical parameter:

model	yt-2600	yt-2800	yt-21000
width of base material	600mm	800mm	1000mm
max.width of printing	560mm	760mm	960mm
printing length	228 -914mm	228 -914mm	228 -914mm
max diameter	450mm	450mm	450mm
printing speed	5 -50m /min	5 -50 m /min	5 -50 m /min

thickness	2.38mm	2.38mm	2.38mm
gross power	8kw	10kw	12kw
gross weight	1800kg	2000kg	2200kg
overall dimension (mm)	2300 × 1860 × 2145	2300 × 2060 × 2145	2300 × 2260 × 2145

本产品的加工定制是是，柔印机类型是层叠式，印刷颜色是双色，操作方式是自动，适用对象是塑料软包装，适用材质是无纺布，品牌是瑞泰，型号是2800，印刷速度是5-50m/min (m/min)，最大印料宽度是800 (mm)，最大印刷宽度是760 (mm)，印刷品长度范围是228-914 (mm)，卷材最大直径是450 (mm)，胶板辊筒周长是330 (mm)，套印精度±是0.15 (mm)，重量是2000 (kg)，外形尺寸是2300 × 2060 × 2145 (mm)，产品类型是全新，售后服务是上门安装调试，保修一年