

# AMPKX 国标网线 CAT5E超五类纯无氧铜0.51网络线300米

产品名称	AMPKX 国标网线 CAT5E超五类纯无氧铜0.51网络线300米
公司名称	深圳市安普网络有限公司
价格	面议
规格参数	品牌:AMPKX 型号:0868 传输速率:1000 ( Kpbs )
公司地址	中国 河南 郑州市金水区 北环路
联系电话	86-0371-60900825 13413912128

## 产品详情

实拍图：

欢迎订做 厂家专业生产

特别提示：因库存多变，拍前请联系客服，以免给您造成不便。

special reminder: due to inventory changes, please contact customer service before the shoot, in order to avoid the inconvenience caused to you.

深圳安普网络线缆厂家--中国著名品牌

shenzhen anpu network cable manufacturers - chinese famous brand

24小时免费拨打工厂热线：0-13413912128

24 hours free calls to factory hotline: 0-13413912128

承接电线，网线，监控线，综合线，电话线，oem生产

to undertake the electric wire, cable, control line, comprehensive line, telephone line, oem production

深圳市安普网络有限公司普宁(网络线缆)电缆厂是一家集开发,生产及销售于一体的现代化企业。拥有12000m<sup>2</sup>现代化厂房,引进全套国外先进生产线和检测设备。公司以雄厚的生产实力和卓越的产品品质赢得广大的客户的高度信赖,跻身于全国线缆行业品牌企业。

shenzhen anpu network co. ltd. of puning (network cable) cable factory is a collection development, production and sales in one of the modern enterprise. 12000m<sup>2</sup> has a modern plant, the introduction of a full set of advanced production line and testing equipment. company with strong production strength and excellent product quality to win the trust of the broad masses of customers, the ranks of the national cable industry brand enterprises.

我们本着“开拓创新,质量为本,以质取胜”的理念,以专业的触角洞悉信息智能化的来临。着眼全国,放眼世界,以诚信的宗旨和坚定信心创造辉煌明天。

we have the spirit of "innovation, quality, quality win" concept, with professional insight into the intelligent information coming. on the national, have the whole world in view, the integrity of purpose and confidence to create a brilliant tomorrow.

本公司专业生产:

this company specialized production:

电线: 线缆

wire: wire and cable

网络线: 五类, 超五类, 六类, 单屏蔽, 双屏蔽, 阻水线缆

network lines: five, five, six, single shielded, double shielded cable, water resistance

电话线: 两芯, 四芯

telephone: two core, four core

监控系列: 同轴电缆, 监控线缆

monitor series: coaxial cable, control cable

联系人: 肖旭浩

contact person: xiao xuhao

联系电话: 13413912128

tel: 13413912128

本产品的品牌是AMPKX, 型号是0868, 传输速率是1000 (Kpbs), 使用温度是0-60 ( ), 储存温度是0-60 ( ), 抗拉强度是100 (N), 抗压强度是100, 适用范围是综合布线, 弱电工程, 电线最大外径是5.

3, 产品认证是CCC, 芯数是8