

三线专业级IP话机 SIP-T22 亿联IP话机 VOIP话机 网络话机

产品名称	三线专业级IP话机 SIP-T22 亿联IP话机 VOIP话机 网络话机
公司名称	广州市八爪鱼网络科技有限公司
价格	面议
规格参数	品牌:亿联 型号:SIP-T22 录音功能:无
公司地址	广东广州市天河区中山大道龙怡苑1310
联系电话	0086-4001188-727

产品详情

亲，如果客服人员没有及时回你的询问，可加微信：gzbzy8

或者qq：12305916 每天24小时在线的！！

sip-t22p

三线专业级ip话机（poe）采用ti titan芯片组及ti 音频引擎；支持3线路，带3个可编程按键；带背光的132x64像素图形液晶，支持中英文等多国语言；高保真(hd)音质: 宽频语音编码，hd手柄，hd免提；xml浏览器，支持轮换制（hot-deskting）；以太网供电（poe）、双网口、耳麦；

产品特性：

采用ti titan芯片组及ti音频引擎带背光132 × 64分辨率图形液晶显示屏三线路，通过broadsoft、avaya、asterisk认证高清（hd）音质：hd 编码,hd手柄,hd免提电话32个按键（含4个软按键）支持blf/bla, sms信息，语言信箱，对话机支持语言设置，xml远程电话簿支持多种自动配置方式: ftp/tftp/http/pnp支持srtp/tls/https等加密协议

话机特性支持3线路、热线、紧急号码呼出支持呼叫等待、通话转接、来电转移通话保持，静音、自动应答、重拨三方通话、免打扰、速拨号xml远程电话簿搜索/导出/导入电话簿、黑名单、通话记录（100条）音量调节、铃声选择国家信号音、系统日志多国语言（20多种）

ip-pbx功能呼叫规则，立即呼出sms短消息，语音信箱，mwi消息提示对话机（intercom）截答（call pickup），call park区别振铃音频特性宽带编码: g.722窄带编码：g.711, g723.1, g726, g.729ab支持vad, cng, aec, plc, ajb, agc等音频处理全双工免提，带自动回音消除

网络特性支持sip v1(rfc2543),v2(rfc3261)协议支持stun内网穿透支持三种ip获取方式：静态ip/dhcp/pppoe拨号支持三种dtmf模式：带内(in-band)、rfc2833、sip info内置http/https web服务器用于配置管理支持ntp时间协议支持telnet内置dns/tftp/ftp客户端

配置管理支持ftp/tftp/http/pnp方式的auto provision支持三种配置模式：网页、话机及自动配置支持ip直拨支持通过sip服务器拨号码支持通过sip服务器拨url地址

安全性支持https协议(客户端/服务器端)支持srtp协议(rfc3711)支持tls(transport layer security)协议支持qos:ieee 802.1p/q(vlan)支持信息验证机制md5/md5-sess支持aes加密协议支持话机锁支持管理员/用户分层模式

物理特性内嵌ti(美国德州仪器)titan芯片组带背光132x64分辨率图形液晶屏外置共32个按键(含4个软按键)5个led指示灯(1个电源指示灯,3个帐号指示灯和1个信息指示灯)1个rj9(4p4c)手柄接口1个rj9(4p4c)耳麦接口2个rj45 10/100m以太网口支持壁挂电源适配器:ac 100-240v输入,dc 5v/1.2a输出支持以太网供电(poe):ieee 802.3af净重:0.77kg功耗:1.4-2.6w净重:0.77kg裸机尺寸:185 x 200 x 90mm操作环境湿度:10-95%储存温度:60 以下

enterprise hd ip phone

sip-t22p

the yealink sip-t22p features an intuitive user-interface and enhanced functionality to make user interaction and operation very easy and efficient. the ti titan chipset and ti leading voip voice engine provide enhanced high-definition audio, outsourced management options, flexible installation and the addition of third-party communications applications. as a cost-effective ip solution, the t22p helps users to streamline their business systems and delivers a powerful, secure and consistent communication experience for both small and large office environments

features
ti titan chipset and ti voice engine 132x64 graphic lcd 3 voip accounts, broadsoft /avaya/asterisk validated hd voice: hd codec, hd handset, hd speaker 32 keys including 4 soft keys sms, voicemail, intercom localized language, xml phonebook ftp/tftp/http, pnp auto-provision srtp/https/tls, vlan, qos poe, headset, wall-mounted

specification

phone features 3 voip accounts, hotline, emergency call call waiting, call transfer, call forward hold, mute, flash, auto-answer, redial 3-way conference, dnd, speed dial phonebook (each record with 3 phone numbers, 300 entries), blacklist xml phonebook search/import/export lists of missed, received, dialed and forwarded calls (100 entries in all) volume adjustment, ring tone selection tone scheme, system log multi-language (more than 20) ip pbx system integration dial plan, dial-now sms, voicemail, mwi intercom call park, call pickup distinctive ringtone codecs and voice features wideband codec: g.722 narrowband codec: g.711, g.723.1, g.726, g.729 abvad, cng, aec, plc, ajb, agc full-duplex speakerphone with aec network features sip v1 (rfc2543), v2 (rfc3261) nat traversal: stun mode dtmf: in-band, rfc2833, sip info proxy mode and peer-to-peer sip link mode ip assignment: static/dhcp/pppoe tftp/dhcp/pppoe

clienttelnet/http/https serverdns clientnat/dhcp servermanagementftp/tftp/http/pnp auto-provisionconfiguration:
browser/phone/auto-provisiondirect ip call without sip proxydial number via sip serverdial url via sip
serversecurityhttps (server/client)srtp (rfc3711)transport layer security (tls)vlan (802.1 pq), qosdigest authentication
using md5/md5-sesssecure configuration file via aes encryptionphone lock for personal privacy protectionadmin/user
configuration modephysical featuresti titan chipset132x64 graphic lcd32 keys including 4 soft keys5 leds: 1xpower,
3xline, 1xmessage1xrj9 handset port1xrj9 headset port2xrj45 10/100m ethernet portswall-mountedpower adapter: ac
100~240v input and dc 5v/1.2a outputpower over ethernet (ieee 802.3af)power consumption: 1.4-2.6wnet weight:
0.77kgdimension: 185 x 200 x 90mmoperating humidity: 10~95%storage temperature: up to 60 ° c

本产品的品牌是亿联，型号是SIP-T22，录音功能是无，来电显示是有，可视功能是无，号码储存功能是有，子机数目是一，接口形式是双网口，外形尺寸是275x220x105（mm），重量是4（kg）