

全自动立式高速覆膜机 水胶、预涂膜多用覆膜机

产品名称	全自动立式高速覆膜机 水胶、预涂膜多用覆膜机
公司名称	玉田县华泰精工机械有限公司
价格	面议
规格参数	加工定制:是 型号:HT1300F 覆膜宽度:1300 (mm)
公司地址	河北省唐山市玉田县孤树镇邢张庄村
联系电话	86-03156482099 15176665689

产品详情

ht1300自动高速水性覆膜机

主要性能特点

大直径带内胆、导向循环预热,压合滚筒,压合面积大,加热均匀、高效、安全,成品亮度高、粘合力强,机械速度可达80米/分。优越的多种复合工艺,水性胶、预涂膜、无胶膜任您选用,全方位满足客户需求。强力热风干燥系统使水胶快速干燥,动态温度控制节约能耗。吸风除尘、静电除粉技术保证覆膜质量。激光雕刻陶瓷网纹辊涂胶,涂胶均匀、轻薄,耐磨、高效。贴合胶辊自动液压升降控制,降低废品率,复合压力大,产品复着牢固、光泽明亮、饱满,无形变,液压站安全稳定。链刀分切,伺服电机驱动,分切准确、速度高、无尾膜、无毛边,同时辅以圆盘刀分切,适用范围更广。

8.收纸采用震动齐纸技术,纸堆更整齐,附纸张计数器。

9.知名品牌plc可编程序控制器,人机界面显示系统与精工机械完美结合,展现了现代的智能气质,操作简便。

ht1300 automatic high-speed water-based laminating machine

features

1.large diameter mirror polished pressure steel roller is heated by oil and drying tunnel steel roller is heated by water .their temperature is controlled by a separate temperature unit beside the laminator. so the surface temperature of the main roller is less changed and accurate. the highest laminating speed is 80m/min.

2. multi-functional laminator is suitable for water-based glue, non-glue film and pre-coated/thermal film.
3. strong hot wind drying system makes glue dry rapidly. dynamic temperature control saves electric energy.
4. static electricity and heating roller powder removing devices keep powder removing effect in a long time.
5. ceramic roller attached glue scraper and glue roller distance adjustment control to ensure the uniformity and thinness of coating. film and glue clutch are controlled by pneumatic device.
6. laminating roller is elevated by hydraulic pressure station automatically to reduce rejection rate, high pressure makes product luster, bright, intangible.
7. flying-knife cutter which is supplemented by disc-knife cutter is driven by servo motor and it is accurate, fast, no rough edges. the scope of application is wider.
8. during high speed running, paper delivery is smooth with the help of paper pressed device. vibrant paper delivery makes paper-pile perfect. paper counter is indispensable.
9. it is controlled by known brand inverter and plc, showed in human-computer interface which is more humanized.

联系我们

公司：玉田县华泰精工机械有限公司

联系地河北省唐山市玉田县孤树镇邢张庄村南
址：

电话：+86-315-6481599

传真：+86-315-6481599

公司邮huatijinggong@163.com

箱：

公司网www.ythtjg.com

址：

联 杨先生 (+86-151 7666 5689)

系人

：

杨女士 (+86-158 3058 0513)

qq客 280788872

服：

本产品的加工定制是是，型号是HT1300F，覆膜宽度是1300（mm），覆膜速度是10-70（米/分钟），电热功率是20-25（Kw），覆膜温度是70-120（ ），适用纸张是100-500g/m²，机重是12（t），外型尺寸是12600×2100×3000（mm），品牌是华泰精工，电机功率是35（Kw），包装是托运底托缠绕膜，类型是自动覆膜机