

美国/日本生产的3400,1600,2500拉钉枪

产品名称	美国/日本生产的3400,1600,2500拉钉枪
公司名称	深圳市龙岗区平湖业俊电子商行
价格	面议
规格参数	加工定制:否 型号:3400,1600,2500 规格:3400,1600,2500
公司地址	深圳市龙岗区平湖街道华南大道一号路华南国际印刷纸品包装物流区(一期)P05栋117号1层2号铺(办公住所)
联系电话	86 755 28234778/81481278 13826587970

产品详情

美国/日本生产的3400,1600,2500拉钉枪

the proset® 2500 tool features many innovative high performance features including a patented "quick disconnect" nose housing and jaw case for rapid cleaning and maintenance of the front end without the need for any tools. with the 2500 "quick disconnect" mandrel collection system (mcs), mandrels are safely collected for easy disposal and cleaner work areas. an air-isolation switch on the mcs prevents air flow when the mcs is disconnected. the tough aluminum casing is designed to prevent damage and enhance the life of the tool. a left or right 90 ° swivel air fitting ensures the tool can be adapted to virtually any workstation configuration, while the "on/off" switch minimizes air consumption. the spring return ensures fast, reliable setting cycles reducing operating cost.

an extended 5" (140mm) front end is also available for extra reach in special setting situations. the proset® 2500 is compatible with other emhart technologies

the proset® 1600 will keep your production lines running at full speed. thanks to the innovative quick disconnect nose housing, the front end components can be serviced in minutes - without tools. with the 1600 mandrel collection system (mcs) model, spent mandrels are instantly collected, and with the quick disconnect system, disposal takes no time, keeping work areas safe and clean with minimal downtime.

this proset® 1600 model also features an innovative left or right, on/off swivel air fitting providing additional flexibility, conserving energy and reducing operating costs. the 1600 will set 2.0 mm micro rivets, 3/32" (2.4mm) and 1/8" (3.2mm) diameter rivets in all materials and up to 5/32" (4.0mm) all steel open end rivets.

features & benefits

ergonomic lightweight polymer construction comfortable two finger, low activation force trigger directional air

exhaust performance high force-to-weight ratio quick disconnect nose housing quick disconnect jaw case quick disconnect mandrel collector economy conserve energy, on/off, left or right swivel air fitting adaptability capable of setting 2.0 mm micro rivets extended 5" long front end for extra reach pop® rivet presenter (rp) compatible

built with ergonomics in mind, this tool features the patented quick disconnect nose housing and jaw case for rapid maintenance of the front end – with no need for tools! the quick disconnect mandrel collection system (mcs) safely collects spent mandrels for easy disposal and cleaner work areas. the air isolation switch on the mcs eliminates air flow when the mcs is disconnected. a rugged aluminum casting is designed to prevent damage and enhances the life of the tool. the left-right 90 ° swivel air fitting ensures the tool can be adapted to any workstation and the “ on/off ” switch minimizes air consumption and noise. a spring return ensures fast, consistent and reliable setting cycles reducing operating costs. the proset® 3400 is compatible with the pop® rivet presenter, the pop® remote mcs system (mcs5000) and pop® specialty heads. the 3400 will set 1/8" (3.2mm), 5/32" (4.0mm), 3/16" (4.8mm) and 1/4" (6.4mm) diameter rivets in all materials including stainless steel high strength structural rivets.

features & benefits:

ergonomic lightweight strong polymer construction comfortable two finger, low activation force trigger directional air exhaust (mcs model) on/off, left or right swivel air fitting performance / economy high force-to-weight ratio quick disconnect nose housing quick disconnect jaw case quick disconnect mandrel collection system spring return for a reliable fast setting cycle adaptability extended 8" (200mm) long front end for extra reach pop® rivet presenter (rp) compatibility pop® remote mandrel collection system (mcs5000) compatible pop® specialty heads (corner head / offset head) compatible safety air-isolation switch during mcs removal

本产品的加工定制是否，型号是3400,1600,2500，规格是3400,1600,2500，类型是单手操作式，全长是55（mm），拉铆力是50（N），配枪头个数是1，适用铆钉直径是1-8（mm），适用范围是拉钉，品牌是POP，属性是属性值