

[AVX钽电容TPS低内阻系列]

产品名称	[AVX钽电容TPS低内阻系列]
公司名称	北京中企同和科技有限公司
价格	面议
规格参数	品牌:VIking光颀TPS低内阻系列 型号:TPS低内阻系列]钽电容] 介质材料:漆膜
公司地址	北京市丰台区太平桥西里27号362室
联系电话	86-01056034197 15313872977

产品详情

低阻抗

容量 0.15uf~1500uf a b c d e v
电压 2.5v~50v

tps

低阻抗

容量 0.15uf~1500uf 电压 a b c d e v
2.5v~50v

[avx钽电容tps低内阻系列]

low esr how to order technical data: all technical data relate to an ambient temperature of +25 ° c capacitance range: 0.15 μ f to 1500 μ f capacitance tolerance: ± 10%; ± 20% rated voltage (vr) +85 ° c: 2.5 4 6.3 10 16 20 25 35 50 category voltage (vc) +125 ° c: 1.7 2.7 4 7 10 13 17 23 33 surge voltage (vs) +85 ° c: 3.3 5.2 8 13 20 26 32 46 65 surge voltage (vs) +125 ° c: 2.2 3.4 5 8 13 16 20 28 40 temperature range: -55 ° c to +125 ° c environmental classification: 55/125/56 (iec 68-2) reliability: 1% per 1000 hours at 85 ° c, vr with 0.1 /v series impedance, 60% confidence level termination finished: sn plating (standard), gold and snpb plating upon request meets requirements of aec-q200 technical specifications case dimensions: millimeters (inches) code eia l ± 0.20 w +0.20 (0.008) h +0.20 (0.008) w1 ± 0.20 a +0.30 (0.012) s min. code metric (0.008) -0.10 (0.004) -0.10 (0.004) (0.008) -0.20 (0.008) a 1206 3216-18 3.20 (0.126) 1.60 (0.063) 1.60 (0.063) 1.20 (0.047) 0.80 (0.031) 1.10 (0.043) b 1210 3528-21 3.50 (0.138) 2.80 (0.110) 1.90 (0.075) 2.20 (0.087) 0.80 (0.031) 1.40 (0.055) c 2312 6032-28 6.00 (0.236) 3.20 (0.126) 2.6 (0.102) 2.20 (0.087) 1.30 (0.051) 2.90 (0.114) d 2917 7343-31 7.30 (0.287) 4.30 (0.169) 2.90 (0.114) 2.40 (0.094) 1.30 (0.051) 4.40 (0.173) e 2917 7343-43 7.30 (0.287) 4.30 (0.169) 4.10 (0.162) 2.40 (0.094) 1.30 (0.051) 4.40 (0.173) f 2312 6032-20 6.00 (0.236) 3.20 (0.126) 2.00 (0.079) 2.20 (0.087) 1.30 (0.051) 2.90 (0.114) max. p 0805 2012-15 2.05 (0.081) 1.35 (0.053) 1.50 (0.059) 1.0 ± 0.10 50 (0.020) 0.85 (0.033) max. (0.039 ± 0.004) r 0805 2012-12 2.05 (0.081) 1.30 (0.051) 1.20 (0.047) 1.0 ± 0.10 50 (0.020) 0.85 (0.033) max. (0.039 ± 0.004) s 1206 3216-12 3.20 (0.126) 1.60 (0.063) 1.20 (0.047) max. 1.20 (0.047) 0.80 (0.031) 1.10 (0.043) t 1210 3528-12 3.50 (0.138) 2.80 (0.110) 1.20 (0.047) max. 2.20 (0.087) 0.80 (0.031) 1.40 (0.055) v 2924 7361-38 7.30 (0.287) 6.10 (0.240) 3.45 ± 0.30 3.10 (0.120) 1.40 (0.055) 4.40 (0.173) (0.136 ± 0.012) w 2312 6032-15 6.00 (0.236) 3.20 (0.126) 1.50 (0.059) max. 2.20 (0.087) 1.30 (0.051) 2.90 (0.114) x 2917

7343-15 7.30 (0.287) 4.30 (0.169) 1.50 (0.059) max. 2.40 (0.094) 1.30 (0.051) 4.40 (0.173)y 2917 7343-20 7.30 (0.287) 4.30 (0.169) 2.00 (0.079) max. 2.40 (0.094) 1.30 (0.051) 4.40 (0.173)更多详情请电话：010-62552280 索要规格书可免费提供样品测试.

本产品的品牌是VIking光颧TPS低内阻系列，型号是TPS低内阻系列]钽电容]，介质材料是漆膜，应用范围是高压，外形是长方形，功率特性是中功率，频率特性是中频，调节方式是可变，引线类型是轴向引出线，允许偏差是 ± 0.1 （%），耐压值是2.5（V），等效串联电阻(ESR)是2.5Vdc-4Vdc（m Ω ），标称容量是atetoanambienttemperatureof+25 $^{\circ}$ C（ μ F），损耗是0.01，额定电压是25Vdc（V），绝缘电阻是0.15 μ Fto1500（m Ω ），温度系数是 $\pm 10\%$; $\pm 20\%$