

# 超微新准系统SYS-1026TT-TF

产品名称	超微新准系统SYS-1026TT-TF
公司名称	深圳市星宏伟业科技有限公司
价格	面议
规格参数	品牌:超微 支持内存容量:4GB 显卡:集成
公司地址	深圳市福田区梅华路105号多丽工业区科技楼604
联系电话	0755-83005001

## 产品详情

world first ddr3, qpi, 1u-twin mainboard integrated ipmi2.0 w/ kvm and dedicated lan

key features1. dual intel® 5500 series xeon® quad/ dual-core, with qpi up to 6.4 gt/s2. intel® 5500 (tylersburg) chipset3. up to 48gb ddr3 1333/ 1066/ 800mhz ecc registered dimm / 24gb unbuffered dimm4. intel® 82576 dual-port gigabit ethernet controller5. 1 (x16) pci-e 2.0 slot6. integrated ipmi 2.0 with kvm and dedicated lan7. integrated matrox g200ew graphics

product skus

mbd-x8dtt-f-b x8dtt-f(bulk pack)

physical stats

form factor dimensions proprietary 16.64" x 6.5 " (42.26cm x 16.51cm)

chassis ( optimized for x8dtt-f)

1u chassis cse-808t-780bcse-809t-7

expansion slots

pci-express 1 (x16) pci-e 2.0 slot

processor/cache		system bios	
cpu	dual 1366-pin lga socket supports up to two intel® 64-bit xeon® processor(s) of the same type below: quad-core intel® xeon® processor 5500 sequence (nehalem-ep processor)	bios type	32mb spi flash eeprom v
qpi	up to 6.4 gt/s	bios features	plug and play (pnp) pci keyboard support
system memory		management	
memory capacity	12x 240-pin dimm socket supports up to 48 gb 1333 / 1066 / 800mhz ddr3 ecc registered memory supports up to 24 gb 1333 / 1066 / 800mhz ddr3 ecc unbuffered memory memory mirroring supported	software	ipmi (intelligent platform v1.5 / 2.0 with kvm support) dognmi
memory type	1333 / 1066 / 800mhz ecc registered / ecc unbuffered ddr3 sdram 72-bit, 240-pin gold-plated dimms	power configurations	acpi power management mechanisms power-on m
dimms sizes	1gb, 2gb, 4gb	pc health monitoring	
memory voltage	1.5 v	cpu	monitors for cpu cores, -stdby, +3.3 stdby, vbat, 6-phase-switching volta
error detection	corrects single-bit errors detects double-bit errors (using ecc memory) supports intel® x4 and x8 single device data correction (sddc)	fan	total of four 4-pin pwm monitoring status monitor for on/off control (4-pin fan only)
on-board devices		temperature	monitoring for cpu and thermal trip support thermal connectors psu i2c temp monitor 2 (tm2) support
chipset	intel® 5500 (tylersburg) chipset ich10r + ioh-36d	led	power fail / overheat led led uid led
sata	intel ich10r sata 3.0gbps controller raid 0, 1, 5, 10 support (windows) raid 0, 1, 10 support (linux)	other features	sddc support
ipmi	support for intelligent platform management interface v.2.0 ipmi 2.0 with virtual media over lan and kvm-over-lan support winbond® wpcm450 bmc	operating environment / compliance	
network controllers	intel® 82576 dual-port gigabit ethernet controllers supports 10base-t, 100base-tx, and 1000base-t, rj45 output intel® i/oat 3 support for fast, scaleable, and reliable networking vmdqs support for better performance of virtualization 1x realtek rtl8201n phy (dedicated ipmi)	rohs environmental spec.	rohs compliant 6/6, pb free operating temperature: 0 to 95 ° f non-operating temperature: -40 ° to 158 ° f operation humidity: 5 to 95% (non
graphics		matrox g200ew	
super i/o	winbond w83527hg chip		
clock generator	932s421 chip		
input / output			
serial ata	six serial ata ports six sata hard drives supported		
lan	2x rj45 lan ports 1x rj45 dedicated ipmi lan port		
usb	2 rear + 1 header (2 ports) 4 total usb ports, 2.0 compliant / 1.1 compliant		
vga		1x vga port	
serial port	1 fast uart 16550 serial port		

parts list (bulk package)

	part number	qty	description
x8dtt-f	mbd-x8dtt-f-b	1	x8dtt-fmotherboard
i/o cable 1	cbl-0044l	2	57.5cm sata flat s-s pbf
driver disk	cdr-x8 1.02	1	driver cd for x8 motherboard

本产品的品牌是超微，支持内存容量是4GB，显卡是集成