超微新准系统SYS-1026TT-TF

产品名称	超微新准系统SYS-1026TT-TF
公司名称	深圳市星宏伟业科技有限公司
价格	面议
规格参数	品牌:超微 支持内存容量:4GB 显卡:集成
公司地址	深圳市福田区梅华路105号多丽工业区科技楼604
联系电话	0755-83005001

产品详情

world first ddr3, qpi, 1u-twin mainboard integrated ipmi2.0 w/ kvm and dedicated lan

key features1. dual intel ® 5500 series xeon ® quad/ dual-core, with qpi up to 6.4 gt/s2. intel ® 5500 (tylersburg) chipset3. up to 48gb ddr3 1333/ 1066/ 800mhz ecc registered dimm / 24gb unbuffered dimm4. intel ® 82576 dual-port gigabit ethernet controller5. 1 (x16) pci-e 2.0 slot6. integrated ipmi 2.0 with kvm and dedicated lan7. integrated matrox g200ew graphics

tes

mo

up

ipr

do
an

product skus	
mbd-x8dtt-f-b	x8dtt-f(bulk pack)
physical stats	
form factor	proprietary
dimensions	16.64" x 6.5 " (42.26cm x 16.51cm)

chassis (optimized for x8dtt-f)	
1u chassis	cse-808t-780bcse-809t-7
expansion slots	
pci-express	1 (x16) pci-e 2.0 slot

processor/cache

cpu	dual 1366-pin lga socketssupports up to twointel ® 64-bit xeon ® processor(s) of the same type below:quad-core intel ® xeon ® processor 5500 sequence (nehalem-ep processor)
qpi	up to 6.4 gt/s

system memory

memory capacity	12x 240-pin dimm socketssupports up to 48 gb 1333 / 1066 / 800mhz ddr3 ecc registered memorysupports up to 24 gb 1333 / 1066 / 800mhz ddr3 ecc unbuffered memorymemory mirroring supported
memory type	1333 / 1066 / 800mhz ecc registered / ecc unbuffered ddr3 sdram 72-bit, 240-pin gold-plated dimms
dimm sizes	1gb, 2gb, 4gb
memory voltage	1.5 v
error detection	corrects single-bit errorsdetects double-bit errors (using ecc memory)supports intel ® x4 and x8 single device data correction (sddc)

on-board devices

chipset	intel ® 5500 (tylersburg) chipsetich10r + ioh-36d
sata	intel ich10r sata 3.0gbps controllerraid 0, 1, 5, 10 support (windows)raid 0, 1, 10 support (linux)
ipmi	support for intelligent platform management interface v.2.0ipmi 2.0 with virtual media over lan and kvm-over-lan supportwinbond ® wpcm450 bmc
network controllers	intel ® 82576 dual-port gigabit ethernet controllersupports 10base-t, 100base-tx, and 1000base-t, rj45 outputintel ® i/oat 3support for fast, scaleable, and reliable networkingvmdqsupport for better performance of virtualization1x realtek rtl8201n phy (dedicated ipmi)
graphics	matrox g200ew
super i/o	winbond w83527hg chip
clock generator	932s421 chip

input / output

serial ata	six serial ata portssix sata hard drives supported
lan	2x rj45 lan ports1x rj45 dedicated ipmi lan port
usb	2 rear + 1 header (2 ports)4 total usb ports, 2.0 compliant / 1.1 compliant
vga	1x vga port
serial port	1 fast uart 16550 serial port

system bios

bios type	32mb spi flash eeprom v
bios features	plug and play (pnp)pci 2 keyboard support

management

software	ipmi (intelligent platforr v1.5 / 2.0 with kvm supp dognmi
power configurations	acpi power managemen mechansimpower-on m

pc health monitoring

cpu	monitors for cpu cores,- stdby, +3.3 stdby, vbat, 6-phase-switching volta
fan	total of four 4-pin pwm monitoringstatus monit monitor for on/off contr control (4-pin fan only)
temperature	monitoring for cpu and thermal trip supportther connectorspsu i2c temp monitor 2 (tm2) suppor
led	power fail / overheat led leduid led
other features	sddc support

operating environment / compliance

rohs	rohs compliant 6/6, pb f
environmental spec.	operating temperature: 1 95 ° f)non-operating ter (-40 ° to 158 ° f)opera 90% (non-condensing)r humidity: 5 to 95% (nor

parts list (bulk package)

	part number	qty	description
x8dtt-f	mbd-x8dtt-f-b	1	x8dtt-fmotherboard
i/o cable 1	cbl-0044l	2	57.5cm sata flat s-s pbf
driver disk	cdr-x8 1.02	1	driver cd for x8 motherboard

本产品的品牌是超微，支持内存容量是4GB，显卡是集成