

复合铝箔岩棉管 热水保温管套棉管 石棉制品 高密度岩棉管

产品名称	复合铝箔岩棉管 热水保温管套棉管 石棉制品 高密度岩棉管
公司名称	顺德区大良鑫莹保温建材经营部
价格	面议
规格参数	材质:岩棉 产地:河北 产品类别:岩棉制品
公司地址	中国 广东 佛山 顺德区 大良红岗广珠路大邑径顺德四建公司综合..
联系电话	86-075726978108 15918132669

产品详情

产品特点及优势features and advantages of products

- 1、高质超细、渣球含量低、导热系数小；
- 2、容重密度范围大（40kg-200kg/ m3）、规格范围广，各项指标均达到或超过国家标准；
- 3、适用范围广，用于建筑、石油、电力、冶金、纺织、国防、交通运输等行业，是管道贮罐、锅炉、烟道、热交换器、风机、车船等工业设备隔热、隔声的理想材料；
- 4、因生产规模大、技术领先，在国内市场上非常畅销，特别是大型重点工程，并远销国外十几个国家的地区。

1. high quality and extra fine, low slag-ball content and low coefficient of heat conductivity;

2. wide range of bulk density (40kg-200kg/ m3), wide range of specifications with all data being within/better than national standards;

3. wide range of applications for construction, petroleum, electric power, metallurgy, textile, national defence, transportation and other industries. ideal material for heat insulation and sound insulation of industrial facilities such as tank , boiler, flue, heat exchanger , blower, vehicles and ships etc;

4. owing to its large-scale production and advanced technology the products are salable in home market, especially for large and key projects. the products are also sold to more than 10 countries/regions abroad.

本产品具有较高强度及较好弹性，具有一定耐压力、经过打褶处理的岩棉板具有较大的拉拔强度，不易起层，大大提高了牢固耐久性。

the products have higher strength and better elasticity. the folded rock wool board with certain compression resistance has greater drawing strength, and it does not tend to peel off and has greatly improved durability.

应用application

有弹性，中等强度岩棉板：适用于建筑墙体/屋顶保温、防火、吸音，如幕墙、内墙隔断、电梯井等。

高强度岩棉板：适用于高、低温的各种条件下，有着很好的承载、抗压特性，尤其适用于大型船舶、容器、烘箱和管道及工业设备的保温、绝热。

耐压岩棉板：能承受巨大的高负载。适用于候机室、大型车间等房顶保温。

elastic mid-strength rock wool board: used for heat preservation, fireproofing and sound absorption for the building wall/roof, such as curtain wall, inner wall partition and elevator hoistway, etc.

high-strength rock wool board: used for various high/low temperature conditions, with good weight-bearing ability and compression-resistance, specially suitable for heat preservation and heat insulation for large ships, tanks, ovens, pipelines and other industrial facilities.

compression-resistant rock wool board: used for roof heat preservation of airport lounge and large workshop as it could bear huge loads.

憎水岩棉板rock wool board hydrophobe

憎水板具有弹性大、耐压强度高的特点，该材料的这种结构和特性提供了最佳的防水控制、良好的绝热和防火性能。容重100-200 kg/ m³，标准规格1000 × 630 × 40-100mm。

hydrophobic board is featured in great elasticity and high compression resistance. such structure and feature of this material could provide best water-proof control, good heat insulation and fireproof properties.

岩棉板被应用于船舶、隔墙板、空调系统管道、吸音设备等对防潮和防水性要求非常高的潮湿环境中。

rock wool boards are used on ships, partition wall board, pipelines of air conditioning systems and sound adsorption equipment etc that work in damp environment and should meet very high demand for their dampproof and waterproof properties.

本产品的材质是岩棉，产地是河北，产品类别是岩棉制品，产品种类是岩棉及其制品，导热系数（常温）是0.035，等级是优，低温弯折是良好，断裂伸长率是良好，抗弯强度是良好，抗压强度是良好，品牌是鑫莹，使用温度是600，芯材是石棉纤维，形态是纤维状，形状是管状，应用范围是建筑保温管道保温工业用保温管，规格是60*30*1000，石棉是防火