

HG系列滚筒刮板干燥机 名正机械

产品名称	HG系列滚筒刮板干燥机 名正机械
公司名称	江阴市名正机械有限公司
价格	面议
规格参数	加工定制:是 品牌:名正机械 型号:HG600
公司地址	江阴市镇澄路1388号
联系电话	13601521160

产品详情

hg系列滚筒刮板干燥机

hg series rolling scratch board drier

high heat efficiency. the principle of heat transfer of the roller drier is heat conduction

and the conducting direction keeps uniform in the whole operation circle. except heat loss of

end cover and radiation loss, all heat can be used for evaporating the damp materials on the

wall of the roller . the efficiency can reach 70-80%.

large operation elasticity and wide application. various drying factors of the drier can be adjusted, such as concentration of feeding liquid,thickness of material film, temperature of heating medium,rotating speed of the roller etc.which can change drying speed of the drier.as these factors have no interrelations each other,it brings great convenience to drying operation.and makes it applicable to dry various materials and to meet different requirements of production.

short drying period.the drying period of materials is normally 10 to 300 seconds,so it is suitable for heat-sensitive materials.it also can be reducing pressure operated if it is put in vacuum vessel.

fast drying rate.as film of materials coated on the wall of the roller is very thin. normal,thickness is 0.3 to 1.5 mm,plus directions of heat and matter transmitting are identical, the vaporing strength on the surface of the film can be 20-70 kg.h₂o/m².h.

注：如客户需要，可为客户设计制造上部进料双滚筒干燥机。

note:we can design double-cylinder with upper feeding in according with the request of customers.

热效率高。因滚筒干燥机传热机理属热传导,传热方向在整个操作周期中保持一致,除盖散热和热辐射损失外,其余热量全都用于筒壁湿料膜的蒸发上,热效率可达70%-80%.

操作弹性大,适用性广。可调整滚筒干燥机的诸多干燥因素。如进料的浓度、涂料料膜的厚度、加热介质的温度、滚筒的转动速度等,都可以改变滚筒干燥机的干燥效率,且诸多因素互无牵连。这给滚筒干燥操作带来很大方便,使之能适应多种物料的干燥和不同产量的要求。

干燥时间短。物料的干燥周期一般只有10-300秒,适合于热敏性物料。若将滚筒干燥机设置在真空中,则可在减压条件下运行。

干燥速率大。由于涂抹于筒壁的料膜很薄,一般在0.3-1.5mm,且传热、传质方向一致,料膜表面可保持20-70kg.h₂o/m².h的蒸发强度。

滚筒干燥机是一种内加热传导型转动连续干燥设备。旋转的滚筒通过其下部料槽,粘附着一定厚度的料膜,热量通过管道输送至滚筒内壁,传导到滚筒外壁,再传导给料膜,使料膜中的湿份得到蒸发、脱湿、使含湿分的物料得到干燥。干燥好的物料被装置在滚筒表面的刮刀铲离滚筒,到置于刮刀下方的螺旋输送机,通过螺旋输送机再将干物料集中、包装。

the drier is a kind of rotating continuous drying equipment with internal heating conducting-style. certain thickness of material film attach to the roller from material liquid vessel under the roller.heat is transferred to the internal wall of the cylinder through pipes and then to the external wall and to materials film,to evaporate the moisture in materials film so as to dry materials. dried products are then scraped off by the blade fixed on the surface of the roller, fall down to the spiral conveyor under the blade, and are conveyed, collected and packed.

可分为二种形式；单筒、双筒干燥机，另外也可按操作压力分常压和减压两种形式。

from it feature.it can be divided into single and double cylinder.otherwise, from its operate press, it can be divided into ordinary press and minus press drier.

适用于化工、染料、制药、食品、冶金等行业液体或较粘稠物料的干燥。

it is suitable for drying liquid raw materials or thick liquid in the field of chemical, dyestuff, pharmaceutical, foodstuff, metallurgy industry and so on.

本产品的加工定制是是，品牌是名正机械，型号是HG600，适用物料是片状，滚筒类型是回转滚筒，应用领域是化工染料制药食品冶金，处理量是40-70（kg/h），初水是80（%），终水是1（%），产量是70（kg/h），重量是1200（kg），规格是600-1800