

# 科瑞型超声波传感器APE-0000-001

产品名称	科瑞型超声波传感器APE-0000-001
公司名称	乐清市罗舸自动化设备有限公司
价格	面议
规格参数	加工定制:是 品牌:ROCK-P+F 型号:【热销】科瑞型超声波传感器APE-0000-001
公司地址	浙江乐清市柳市大兴西路450号 嘉城花园B栋1单元601
联系电话	86 0577 83272579 18968973762

## 产品详情

- 1.本公司专业销售各类进口超声波传感器。如倍加福超声波传感器、宝盟超声波传感器、md超声波传感器、科瑞超声波传感器.....
- 2.本公司罗舸自动化设备，专业研发超声波传感器，在技术上处于国内领先的位置，产品能够替代国外各类高端超声波传感器的使用。
- 3.本公司联系信息：0577-83272579，0577-83272576，手机：18968973762，朱先生，期待所有商家的联系，我们会在质量和技术上给诸位带来惊喜。

### 产品阐述

single head system	
general specifications	
sensing range	30 ... 500 mm
adjustment range	50 ... 500 mm
unusable area	0 ... 30 mm 1)
standard target plate	100 mm x 100 mm
transducer frequency	approx. 380 khz
electrical specifications	
operating voltage	10 ... 30 v dc , ripple 10 %ss
no-load supply current	30 ma
input	
input type	1 pulse input for transmitter (active): < 5 v (ub > 15 v)1- 10 v ... +ub (ub > 15 v)0-lev 1/3 ub (10 v < ub < 15 v)1-l > 2/3 ub ... +ub (10 v < ub <

pulse length		5 ... 100 $\mu$ s (typ. 50 $\mu$ s) 2)
pause length		50 x pulse length
impedance		10 kohm internal connected
output		1 pulse output for echo run
output type		proofopen collector pnp with = 22 kohmlevel 0 (no echo) detected): (+ub-2 v)
rated operating current		15 ma , short-circuit/overload
temperature influence		the echo propagation time:
approvals and certificates		
ul approval		culus listed, general purpose
csa approval		ccsaus listed, general purpose
ambient conditions		
ambient temperature		-25 ... 85 $^{\circ}$ c (-13 ... 185 $^{\circ}$ f)
storage temperature		-40 ... 85 $^{\circ}$ c (-40 ... 185 $^{\circ}$ f)
mechanical specifications		
connection type		connector m12 x 1 , 4-pin
protection degree		ip67
material	housing	nickel plated brass; plastic cover
	transducer	epoxy resin/hollow glass sphere polyurethane foam
mass		140 g

本产品的加工定制是是，品牌是ROCK-P+F，型号是【热销】科瑞型超声波传感器APE-0000-001，种类是声波，材料是聚合物，材料物理性质是绝缘体，材料晶体结构是多晶，制作工艺是集成，输出信号是模拟型，防护等级是IP67，线性度是根据产品大小距离去设定（%F.S.），迟滞是所设开关距离的1%（%F.S.），重复性是 1%（%F.S.），灵敏度是正常状态，漂移是满量程值的正负1.5%，分辨率是400kHz