

GUD型电动高真空球阀-上海吉迈阀门制造

产品名称	GUD型电动高真空球阀-上海吉迈阀门制造
公司名称	上海吉迈阀门制造有限公司
价格	面议
规格参数	
公司地址	浦东新区泥城镇新城路2号24幢N2374室
联系电话	021-51078382 15000726608

产品详情

gud型电动高真空(压力)球阀 专业生产gud型电动高真空(压力)球阀价格低, 型号全 产品说明 服务承诺 订货流程 上海吉迈阀门制造有限公司主要生产 gud型电动高真空(压力)球阀 也是国内真空阀门生产商之一。公司经营范围:阀门,管件,流体设备的生产,加工,销售,管道配件,建筑材料,五金交电,自控设备的销售,从事货物及技术的进出口业务! 欢迎新老客户来电,来函,我们将竭诚为您提供满意的服务! gud型 - 电动高真空(压力)球阀 gud型电动高真空(压力)球阀是以电动装置驱动阀杆与球芯来执行启闭动作,达到接通或切断真空(压力)系统管路中的介质流。应用于真空、乳制品、酒业、生物工程、食品、制药、饮料、化妆品及化工领域。 gud electromagnetism vacuum air valve gud electric high vacuum(pressure)ball valve uses electric device to drive the stem and ball for open and close, thus to put through or cut off the medium flow in vacuum(pressure)pipeline. it is used in the areas of vacuum, dairy products, breweries, biological engineering, foddstuff, pharmaceuticals, drinks, cosmetics and chemicals. 主要技术性能 main technical performance 阀门漏率: valve leak rate 1.3×10^{-4} pa.l/s. 适用温度: applicable temperature $-30 \sim +150$ $-30 \sim +150$ (ppl密封) 关闭时间: close time 30s 适用范围: applicability 连接型式 loose flange 使用压力范围(pa) 活套法兰(gb6070、jb919) $0.6 \times 10^6 \sim 1.3 \times 10^{-4}$ 焊接法兰(gb6070、jb919) $1.6 \times 10^6 \sim 1.3 \times 10^{-4}$ 快卸法兰(gb4982) $0.1 \times 10^6 \sim 1.3 \times 10^{-4}$ 螺纹连接 threaded connection $1.6 \times 10^6 \sim 1.3 \times 10^{-4}$ 主要零件材料 materials of main parts 阀体、阀盖、阀杆: 不锈钢 密封件: 四氟乙烯、氟橡胶、ppl。 body, disc and stem: stainless steel. sealing element: nbr, viton, ppl. construction fights (mm) 外形及连接尺寸(mm)(jb919) overall and connection dimensions(mm) 螺纹连接的外形及连接尺寸(图一) model 型号 dn g h e l gud-10(g) 10 1/4" 153 157 68 gud-16(g) 16 1/2" 172 157 72 gud-20(g) 20 3/4" 178 157 82 gud-25(g) 25 1" 187 157 90 gud-32(g) 32 1-1/4" 206 157 112 gud-40(g) 40 1-1/2" 212 157 120 gud-50(g) 50 2" 265 157 145 gud-63(g) 63 2-1/2" 305 207 185 gud-80(g) 80 3" 330 207 210 gud-100(g) 100 4" 350 207 268 活套法兰连接(gb6070)(图二) model 型号 dn d do h e l n- c gud-10(f) 10 55 40 153 157 84 4- 6.6 gud-16(f) 16 60 45 172 157 84 4- 6.6 gud-25(f) 25 70 55 187 157 114 4- 6.6 gud-32(f) 32 90 70 206 157 140 4- 9 gud-40(f) 40 100 80 212 157 160 4- 9 gud-50(f) 50 110 90 265 157 170 4- 9 gud-63(f) 63 130 110 305 207 195 4- 9 gud-80(f) 80 145 125 330 207 203 8- 9 gud-100(f) 100 165 145 350 207 280 8- 9 快卸法兰连接(gb4982)(图三) model 型号 dn d1 d h e l gud-10(kf) 10 12.2 30 153 157 84 gud-16(kf) 16 17.2 30 172 157 84 gud-25(kf) 25 26.2 40 187 157 114 gud-32(kf) 32 34.2 55 206 157 140 gud-40(kf) 40 41.2 55 212 157 160 gud-50(kf) 50 52.2 75 265 157 170 订货需提供产品参数: 产品使用介质 产品工作温度 产品连接方式 产品使用压力 产品是否带附件以便我们选型报价 若已经由设计单位选定产品型号,请按产品型号直接向我司销售部订购。 当使用的场合非常重要或环境比较复杂时,请您尽量提供设计图纸和详细参

数，由我们的阀门专家为您审核把关。具体订货详情请进入：

本页名称：gud型电动高真空(压力)球阀 本页网址：http://www.famen058.com/valve_product_207.html

官方网站：<http://www.famen058.com>