

强力双面胶带、3M胶带、艾柯特胶带、综研胶带

产品名称	强力双面胶带、3M胶带、艾柯特胶带、综研胶带
公司名称	宁波海曙艾柯特贸易商行
价格	32.00/平方米
规格参数	品牌:3M 型号:500 2600:3800
公司地址	海曙区穆家巷28号506室
联系电话	0574-87487320 13605882674

产品详情

宁波艾柯特强力胶带产品展示：

1) 强力双面胶带：

材料：无纺布，棉纸（白色，黑色或彩色胶带）

厚度：0.07mm~0.42mm等，

性能：高粘结强度，性能稳定。耐温，耐溶剂性能良好。

适用领域：汽车，电器、手机、电脑等装饰件及产品内外零部件的固定。

highly adhesive double-sided tape:

material: non-woven (white, black or colored tape)

thickness: 0.09mm ~ 0.42mm

performance: highly adhesive strength, stable performance. temperature resistance, solvent good performance.

application: automotive interior and exterior decorative parts, electrical appliances, decoration of mobile phones, computers, and fix products components.

2) vhb胶带：

材料：丙烯酸

厚度：0.25mm, ~2.2mm,等

性能：粘着强度高，保持性能好，耐高温；起到固定，密封，缓冲等作用。

适用领域：汽车内外装饰件，电器、手机、电脑等装饰件及产品内外零部件的固定。

vhb acrylic tape:

carriers: acrylic

thickness: 0.25mm ~ 2.2mm

performance: highly adhesive, maintain good performance, good temperature resistance; function on fixed, sealing, buffering and so on.

applications: automotive interior and exterior decorative parts, electrical appliances, decoration of mobile phones, computers, and fix products components.

3) 泡棉胶带：

材料：pe，pu，epdm等海绵+进口胶粘剂

厚度：0.25mm~4.0mm等

性能：粘着强度高，保持性能好，耐高温；起到固定，密封，缓冲等作用。

适用领域：汽车内外装饰件，电器、手机、电脑等装饰件及产品内外零部件的固定。

foam double-sided tape:

carriers: pe, pu, epdm, and glue importing

thickness: 0.25mm ~ 4.0mm, etc.

performance: highly adhesive, maintain good performance, good temperature resistance; function on fixed, sealing, buffering and so on.

applications: automotive interior and exterior decorative parts, electrical appliances, decoration of mobile phones, computers, and fix products components.

ctrical appliances, electronics, ,

4) 薄膜胶带：

材料：pet，pvc，pp等薄膜+日本进口胶粘剂

厚度：0.25mm~1.2mm等

性能：粘着强度高，保持性能好，耐高温；起到固定，密封，绝缘,消音等作用。

适用领域：汽车内外部件，电器、手机、电脑等装饰件,薄膜开关,面板及产品内外零部件的固定。

film tape:

material: pet, pvc, pp, and glue importing from japan

thickness: 0.25mm ~ 1.2mm

performance: highly adhesive, maintain good performance, good temperature resistance; function on fixed, sealing, insulation and muffling and so on.

applications: automotive interior and exterior decorative parts, electrical appliances, decoration of mobile phones, computers, film switch, board and fix products components.

5).防水密封绝缘胶带：

材料：丁基胶

厚度：0.8mm~5mm

性能：密封性能优良,耐老化性

适用领域：适用于多种管道焊缝、接头、三铜、弯头、死角部位的填补，以利于胶带的平滑过渡缠绕。建筑,汽车,电器绝缘密封防水等用途

waterproof sealing tape:

material: butyl rubber

thickness: 0.8mm ~ 5mm

performance: excellent sealing performance, anti-aging

applications: suitable for filling a variety of pipeline welds, joints, three copper, elbow, dead parts, in order to facilitate a smooth transition of wound tape. waterproof sealing on construction, automotive, electrical insulation and others.

6). 保护膜：

材料：pe，pet，pp

厚度：0.04mm~0.12mm

性能：透明度高，抗刮拉性能好。有高中低粘着强度。剥离后不残胶，无鬼影。

适用领域：汽车，电器，电子产品生产及销售过程中表面的保护，部件临时固定等。

protective tapes:

carriers: pe, pet, pp

thickness: 0.04mm ~ 0.12mm

features: high transparency, anti-scratch pull good performance. there is three grade adhesive including lower, middle and high. no adhesive residue after peeling, no ghosting.

application: protecting surface of auto, electrical appliances, electronic products during production and selling, temporary fixation for components.

7). 耐高温美纹纸胶带：

材料：皱纹纸（各种颜色）

厚度：0.15mm,0.18mm

性能：耐温度180度,230度.剥离后不残胶.

适用领域：汽车,电器等部件焊锡遮蔽保护，产品固定

high temperature masking tape:

carriers: crepe paper (various colors)

thickness: 0.15mm, 0.18mm

performance: resistance temperature of 180 degrees, 230 degrees. no adhesive residue after peeling.

application: masking protection some parts of auto, electrical appliance when soldering tin; product fixed.

8). 异型胶带：

材料：pe，pu，epdm等海绵+日本进口胶粘剂

厚度：0.25mm~10mm等

性能: 粘着强度高，保持性能好，耐温优良；起到固定，密封，缓冲,消音等作用。

适用领域：汽车内外部件，电器、手机、电脑等装饰件及产品内外零部件的固定。

single-sided foam tape:

material: pe, pu, epdm, and glue importing from japan

thickness: 0.25mm ~ 10mm

performance: high strength adhesive to maintain good performance, excellent heat resistance; function on fixed, sealing, cushioning, silencers and so on.

applications: automotive interior and exterior decorative parts, electrical appliances, decoration of mobile phones, computers, and fix products components.

9).纤维胶带：

材料：玻璃纤维网（直条型，井字型，单面或双面）

厚度：0.12mm~0.23mm

性能：粘着性能强，抗拉性能好，不残胶，剪切时不变形

适用领域：用于家具，木材，钢铁，船舶，机械，电器，电子等行业的重包装、部件固定、产品定位等。

glass fiber tape:

carriers: glass fiber net (straight bar, well-shaped, single-sided or double-sided)

thickness: 0.12mm ~ 0.23mm

performance: strong adhesive properties, good resistance tensile strength, non-residue adhesive, not shear deformation.

applications: used for heavy packaging, components fixed, product positioning on furniture, wood, steel, shipbuilding, machinery, etc

10). 铜箔,铝箔胶带：

材料：铜箔,铝箔

厚度：0.06mm,0.085mm,0.12mm等

性能：粘着性能好,可以制成导电或不导电的胶带。

适用领域：适用于电脑,电器,显示器,变压器，线缆，管道等部件粘接.包扎。可以消除电磁干扰emi,隔离电磁波。

copper foil, aluminum foil tape:

carriers: copper foil, aluminum foil

thickness: 0.06mm, 0.085mm, 0.12mm

performance: good adhesion properties, can be made conductive or non-conductive tape.

applications: suitable for felting or bonding of computers, electrical appliances, monitors, transformers, cables, pipes.
bandaging. it can eliminate electromagnetic interference eml, isolation electromagnetic waves.