

# 1550nm1x2,2x2保偏耦合器

产品名称	1550nm1x2,2x2保偏耦合器
公司名称	四川伏托尼科技有限公司
价格	300.00/支
规格参数	品牌:Photonic 型号:1310/1550nm1x2(2x2)保偏耦合器
公司地址	四川省绵阳市一环路西段125号
联系电话	0816-8013506 13035673260

## 产品详情

1310/1550nm1x2(2x2)保偏耦合器

1x2(2x2) fused pm fiber standard coupler

features	
low excess loss & low insertion loss	
high extinction ratio	
high stability and reliability	
application	
optical amplifier,	
power monitoring	
coherent communication	
fiber gyroscope	
fiber sensor	

specification

parameter	p grade	a grade	p grade	a grade	p grade
central wavelength (nm)	1310, 1550		980,1064		
bandwidth (nm)	± 20				
typ. excess loss (db)	0.2	0.3	0.6	0.8	0.6
max.excess loss (db)	0.4	0.6	0.8	1.0	0.8
er (db)	20	17	18	16	18
directivity (db)	55				
operating temperature( )	-40 ~ +85				
storage temperature ( )	-40 ~ +85				

for device with connector, il is 0.3db higher, rl is 5db lower, er is 2db lower. the default connector key is aligned to slow axis. package information

configuration	1x2 or 2x2				
fiber length	0.8m, others on request				
fiber type	panda fiber				
pigtail type	250 μ m bare fiber	900 μ m loose tube		900 μ m/2mm/3mm	
dimensions(mm)	3.0 × 54	3.0 × 70		90x16x	