

供应1310nm1x2 2x2保偏分路器分路器

| | |
|------|--------------------------------------|
| 产品名称 | 供应1310nm1x2 2x2保偏分路器分路器 |
| 公司名称 | 四川伏托尼科技有限公司 |
| 价格 | 300.00/支 |
| 规格参数 | 品牌:Photonic 型号:1310nm1x2 2x2保偏分路器 |
| 公司地址 | 四川省绵阳市一环路西段125号 |
| 联系电话 | 0816-8013506 13035673260 |

产品详情

供应1310nm1x2 2x2保偏分路器

1x2(2x2) fused pm fiber standard coupler

| | |
|--------------------------------------|--|
| features | |
| low excess loss & low insertion loss | |
| high extinction ratio | |
| high stability and reliability | |
| application | |
| optical amplifier, | |
| power monitoring | |
| coherent communication | |
| fiber gyroscope | |
| fiber sensor | |

specification

| parameter | p grade | a grade | p grade | a grade | p grade |
|--------------------------|------------|---------|----------|---------|---------|
| central wavelength (nm) | 1310, 1550 | | 980,1064 | | |
| bandwidth (nm) | ± 20 | | | | |
| typ. excess loss (db) | 0.2 | 0.3 | 0.6 | 0.8 | 0.6 |
| max.excess loss (db) | 0.4 | 0.6 | 0.8 | 1.0 | 0.8 |
| er (db) | 20 | 17 | 18 | 16 | 18 |
| directivity (db) | 55 | | | | |
| operating temperature() | -40 ~ +85 | | | | |
| storage temperature () | -40 ~ +85 | | | | |

for device with connector, il is 0.3db higher, rl is 5db lower, er is 2db lower. the default connector key is aligned to slow axis. package information

| | | | | | |
|----------------|-------------------------|--------------------|--|-----------------|--|
| configuration | 1x2 or 2x2 | | | | |
| fiber length | 0.8m, others on request | | | | |
| fiber type | panda fiber | | | | |
| pigtail type | 250 μ m bare fiber | 900 μ m loose tube | | 900 μ m/2mm/3mm | |
| dimensions(mm) | 3.0 × 54 | 3.0 × 70 | | 90x16x | |