

供应780 850nm1x22x2保偏耦合器

产品名称	供应780 850nm1x22x2保偏耦合器
公司名称	四川伏托尼科技有限公司
价格	300.00/支
规格参数	品牌:Photonic 型号:780 850nm1x2 2x2保偏耦合器
公司地址	四川省绵阳市一环路西段125号
联系电话	0816-8013506 13035673260

产品详情

1x2(2x2) fused pm fiber standard coupler

features

low excess loss & low insertion loss

high extinction ratio

high stability and reliability

application

optical amplifier,

power monitoring

coherent communication

fiber gyroscope

fiber sensor

specification

parameter p grade a grade p grade a grade p grade a grade

central wavelength (nm) 1310, 1550 980,1064 780,850

bandwidth (nm) ± 20

typ. excess loss (db) 0.2 0.3 0.6 0.8 0.6 0.8

max.excess loss (db) 0.4 0.6 0.8 1.0 0.8 1.0

er (db) 20 17 18 16 18 16

directivity (db) 55

operating temperature() -40 ~ +85

storage temperature () -40 ~ +85

for device with connector, il is 0.3db higher, rl is 5db lower, er is 2db lower. the default connector key is aligned to slow axis. package information

configuration 1x2 or 2x2

fiber length 0.8m, others on request

fiber type panda fiber

pigtail type 250 μ m bare fiber 900 μ m loose tube 900 μ m/2mm/3mm loose tube

dimensions(mm) 3.0 \times 54 3.0 \times 70 90x16x9