

# 中心波长1064nm1x4保偏耦合器

|      |                                      |
|------|--------------------------------------|
| 产品名称 | 中心波长1064nm1x4保偏耦合器                   |
| 公司名称 | 四川伏托尼科技有限公司                          |
| 价格   | 300.00/支                             |
| 规格参数 | 品牌:Photonic<br>型号:中心波长1064nm1x4保偏耦合器 |
| 公司地址 | 四川省绵阳市一环路西段125号                      |
| 联系电话 | 0816-8013506 13035673260             |

## 产品详情

1x4, 1x8 , pm filter coupler module

中心波长1064nm1x4保偏耦合器

specifications

parameters unit values

type 1x4 1x8

center wavelength nm 1310,1550 1064 1310,1550 1064

operating wavelength range nm  $\pm 30$

max. insertion loss db 7.5 8.0 11.0 11.5

min.wdl db 0.5

uniformity db 0.8 1.0

min. extinction ratio both of axis working db 20 17

fast axis blocked db 22 22

min. return loss db 50

directivity db 50 45

temperature dependent loss db/ 0.006 0.008

max. optical power(cw) mw 300

max. tensile load n 5

fiber type pm panda fiber

operating temperature -5~+70

storage temperature -40~+85

package dimensions mm 160x140x10 160x160x10

## features

low insertion loss

high return loss

high extinction ratio

high reliability

## applications

communication systems

test instrumentations

fiber sensors

research

for device with connector, il is 0.3db higher, rl is 5db lower, er is 2db lower.  
the default connector key is aligned to slow axis.