

Photonic1310nm1x8保偏耦合器

产品名称	Photonic1310nm1x8保偏耦合器
公司名称	四川伏托尼科技有限公司
价格	3000.00/个
规格参数	品牌:Photonic 型号:Photonic1310nm1x8保偏耦合器
公司地址	四川省绵阳市一环路西段125号
联系电话	0816-8013506 13035673260

产品详情

1x4, 1x8 , pm filter coupler module

specifications

parameters unit values

type 1x4 1x8

center wavelength nm 1310,1550 1064 1310,1550 1064

operating wavelength range nm \pm 30

max. insertion loss db 7.5 8.0 11.0 11.5

min.wdl db 0.5

uniformity db 0.8 1.0

min. extinction ratio both of axis working db 20 17

fast axis blocked db 22 22

min. return loss db 50

directivity db 50 45

temperature dependent loss db/ 0.006 0.008

max. optical power(cw) mw 300

max. tensile load n 5

fiber type pm panda fiber

operating temperature -5~+70

storage temperature -40~+85

package dimensions mm 160x140x10 160x160x10

features

low insertion loss

high return loss

high extinction ratio

high reliability

applications

communication systems

test instrumentations

fiber sensors

research

for device with connector, il is 0.3db higher, rl is 5db lower, er is 2db lower.
the default connector key is aligned to slow axis.