

代理PICO 微型军工变压器、DC-DC/AC-DC电源模块

产品名称	代理PICO 微型军工变压器、DC-DC/AC-DC电源模块
公司名称	深圳市立维创展科技有限公司
价格	面议
规格参数	应用范围:隔离 种类:其他 品牌:PicoElectronics
公司地址	深圳市福田区福虹路福华大厦626
联系电话	86-075583642657/83050846 18902857268

产品详情

深圳市立维创展科技有限公司独家代理美国pico电感、变压器、dc-dc电源模块、ac-dc电源模块，该产品体积小，工作温度范围宽，可达到-55 ——+85 、电压伏差大，可靠性高。用于航空航天、射频微波通信、石油勘探及工业控制设备，船舶通信电台,移动通信基站、直放站、卫星通信、有线电视、雷达及仪器仪表等领域。

如有需要请联系：张宇 电话：0755-83050846 15817297155 qq：2392507165

n系列及k系列规格参数：

mil-prf-27:all units manufactured to mil-prf-27, grade 5, class s.frequency response: $\pm 3\text{db}$, 150 hz - 75 khz at 1.0 milliwatt. (when primary impedance greater or equal to 50k ohms, $\pm 3\text{db}$ 150 hz to 20 khz)maximum distortion:5% with rated power level at 1 khz, 400 hz and 150 hz.dielectric strength:all units tested at 200 v rms.insulation resistance:greater than 10,000 megohms at 300 v dc.weight:7.5 grams.operating temperature:-55 ° c to +130 ° cterminals:solid .016 diameter conductor. solderability per mil-std-202 method 208.thermal shock:25 cycles, method 107, mil-std-202, test condition -55 ° c. to +130 ° c

pico电源模块中国总代----深圳市立维创展科技有限公司

特性：

I 3种不同系列的设计

I 70 ° 环境下有1.25 w 的输出功率

I 超微型尺寸0.500” 高度,5.0克重量,0.125立方英寸体积

I 6种输入电压5, 12, 15, 24, 28, and 48 vdc

I mil-std 883 options available

I 没有散热器或电气降额要求

相关型号

: 5av1500 , 5av2000 , 5av2500 , 5av3000 , 5av3500 , 5av4000 , 5av4500 , 5av5000 , 5av1500 , 5av2000 , 5av2500
0 , 12av3000 , 12av3500 , 12av4000 , 12av4500
, 12av5000 , 15av1500 , 15av2000 , 15av2500 , 15av3000 , 15av3500 , 15av4000 , 15av4500
, 15av5000 , 24av1500 , 28av2000 , 24av2500 , 24av3000 , 24av3500 , 24av4000 , 24av4500
, 24av5000 , 28av1500 , 28av2000 , 28av2500 , 28av3000 , 28av3500 , 28av4000 , 28av4500
, 28av5000 , 48av1500 , 48av2000 , 48av2500 , 48av3000 , 48av3500 , 48av4000 , 48av4500 , 48av5000 ,

具体型号如下 :

k-7203k-7205k-7210k-7215k-7218k-7220k-7225k-7228k-7230k-7235k-7240k-7245k-7250k-7255k-7260k-7265k-7270k-7275k-7280k-7285k-7290k-7295k-7300k-7305k-7310k-7315k-7320k-7325k-7330k-7335k-7340k-7342k-7344k-7345k-7347k-7350k-7355k-7360k-7365k-7367k-7370k-7375k-7380**k-7385**k-7386**k-7387**k-7390k-7395k-7400k-7405k-7410k-7415k-7417**k-7420k-7425k-7430k-7435k-7440k-7445k-7450k-7455k-7460k-7465k-7470k-7475k-7480k-7483k-7485k-7490k-7495k-7497k-7500k-7505k-7510k-7512k-7514**k-7515k-7520k-7525k-7530k-7535k-7540k-7545k-7550k-7555k-7560k-7565k-7570k-7575k-7580k-7585k-7590k-7595k-7600k-7605k-7610k-7615k-7620k-7625k-7630k-7635k-7640k-7645k-7650k-7652k-7655k-7660k-7665k-7670k-7675k-7680k-7685k-7690k-7695k-7700k-7705k-7710k-7715k-7720k-7725k-7730k-7732k-7734k-7735k-7740k-7745k-7750k-7778k-7779k-7780k-7785k-7787k-7789k-7790k-7795k-7800k-7805k-7810k-7813k-7825k-7830k-7835k-7837k-7840

n系列型号如下 :

n-6203n-6205n-6210n-6215n-6218n-6220n-6225n-6228n-6230n-6235n-6240n-6245n-6250n-6255n-6260n-6265n-6270n-6275n-6280n-6285n-6290n-6295n-6300n-6305n-6310n-6315n-6320n-6325n-6330n-6335n-6340n-6342n-6344n-6345n-6347n-6350n-6355n-6360n-6365n-6367n-6370n-6375n-6380**n-6385**n-6386**n-6387**n-6420n-6425n-6430n-6435n-6440n-6445n-6450n-6455n-6475n-6480n-6483n-6485n-6490n-6495n-6597n-6500n-6505n-6510n-6512n-6514**n-6515n-6520n-6525n-6530n-6535n-6540n-6545n-6550n-6555n-6560n-6565n-6570n-6575n-6580n-6585n-6590n-6595n-6600n-6605n-6610n-6615n-6620n-6625n-6630n-6635n-6640n-6645n-6650n-6652n-6655n-6660

参见公司网址www.leadwaytk.comwww.picoelectronics.com

本产品的应用范围是隔离, 种类是其他, 品牌是PicoElectronics, 型号是N-6386, 封装形式是插件电感, 绕线形式是其他, 导磁体性质是其他, 磁芯形状是其他, 工作频率是高频, 安装方式是立式密封, 骨架材料是陶瓷, 品质因数Q是1, 电感量是1, 允许误差是1, 感抗XL是1 (), 额定电流是1 (mA), 分布电容是1 (F), 标称电压是1 (V)