

SinoV-X508-8-32 语音网关

产品名称	SinoV-X508-8-32 语音网关
公司名称	深圳市源创通信技术有限公司
价格	5400.00/台
规格参数	品牌:SINOVOIP 型号:SinoV-X508-8/32 GSM: 850/900/1800/1900MHz Quad-band GSM Cellular Netwo
公司地址	深圳市南山区南油创业路南中兴综合楼5层北
联系电话	0755-26475332 13411986228

产品详情

sinov-x508-8/32 goip 8 gsm/cdma/wcdma gateway
type : sinov-x508 contact with cherry, email sinovoip(at)foxmail.com or 13411986228 description :

the sinov-x500 is an analog gsm/cdma/wcdma cellular voip gateway that helps directly interconnect a sip-supporting voip network with gsm/cdma/wcdma networks.

introduction

the sinov-x500 is an analog gsm/cdma/wcdma cellular voip gateway that helps directly interconnect a sip-supporting voip network with gsm/cdma/wcdma networks.

function:

1,support 4/8 channels 850/900/1800/1900mhz quad-band gsm, 450mhz or 800/1900mhz dual-band cdma, 850/900/1800/1900/2100mhz wcdma cellular network

2,sms receiving/batch sending, at command compatible

3,support sip registration and peer-to-peer

4,support encryption: rc4, vos and sinov private etc.

5,support hotline, phone book, speed dial, dial plan

6,update firmware by local or internet

7,field proven compatible with asterisk-based softswitches

model	sinov-504g	sinov-508g	sinov-504c	sinov-508c	sinov-5
number of channels	4gsm	8gsm	4cdma	8cdma	4wcdma
frequency	850/900/1800/1900mhz		450mhz or 800/1900mhz		850/900
call control protocols	sip				
voice codecs	g.729a, g.723.1, g.711 a/ulaw				
network protocols	ipv4, tcp, udp, pppoe, dhcp, dns, nat, telnet, http, ftp, tftp				
configuration and maintenance	<ul style="list-style-type: none">- web-based gui- console, telnet command line- centralized network management				
firmware update	local file, ftp, tftp and http				
telephony features	<ul style="list-style-type: none">- hot-line call- dial plan- speed dial- phone book- cdr				

	<ul style="list-style-type: none"> - lcr - white list
telephony signaling	<ul style="list-style-type: none"> - dtmf tone detection/generation - dtmf relay: in-band, rfc 2833 and sip info - call forward: unconditional, no answer and busy - n-way conferencing - caller id display/generation, mobile number portability
voice quality	<ul style="list-style-type: none"> - echo cancellation - silence suppression(voice activity detection, comfortable noise generation) - adaptive jitter buffer
number of ports	<ul style="list-style-type: none"> - 1 wan 10/100base-t ethernet(rj-45 connector) - 1 lan 10/100base-t ethernet(rj-45 connector) - 1 console(rj-11 connector)
leds	1 power and 8 groups of signal strength and running indicator
power supply	100-240vac, 50 - 60 hz
dimensions	<ul style="list-style-type: none"> - rack mountable 1u chassis(compatible with 19" rack) - width: 482mm - height: 44mm - depth: 210mm
weight	2.5kg
operating environment	<ul style="list-style-type: none"> - operating temperature: 0 - 50 ° c - operating humidity: 10 – 90%
warranty	12 months