

3590S-2-202L BOURNS精密电位器

产品名称	3590S-2-202L BOURNS精密电位器
公司名称	深圳市博恩斯科技有限公司
价格	29.90/个
规格参数	加工定制:是 品牌:BOURNS/邦思 型号:电3590S-2-202L
公司地址	深圳市福田区华强北街道华富路南光大厦1210
联系电话	13316826686 13714422322

产品详情

3590s技术参数

电气特性 (electrical characteristics) 标准阻值范围(standard resistance range)200 to 100k ohms 阻值允许偏差(resistance tolerance) $\pm 5\%$ 独立线性度(independent linearity)..... $\pm 0.25\%$ 有效旋转角度(effective electrical angle).....3600 ° +10 ° , -0 ° 最小阻值(absolute minimum resistance)1 ohm or 0.1 % maximum (whichever is greater) 噪音(noise).....100 ohms enr maximum 耐电压(dielectric withstanding voltage)(mil-std-202, method 301) 海平面 (sea level)1,500 vac minimum 额定功率(power rating)(voltage limited by power dissipation or 450 vac, whichever is less) +40 ° c.....2 watts +125 ° c.....0 watt 绝缘电阻(insulation resistance)(500 vdc).....1,000 megohms minimum 分辨率(resolution)see recommended part numbers 环境特性(environmental characteristics) 工作温度范围(operating temperature range).....+1 ° c to +125 ° c 储存温度范围(storage temperature range).....-55 ° c to +125 ° c 温度系数范围(temperature coefficient over storage temperature range2) ± 50 ppm/ ° c maximum/unit 震动(vibration).....15 g 电刷返回(wiper bounce).....0.1 millisecond maximum 冲击(shock).....50 g 高温负荷寿命(load life).....1,000 hours, 2 watts 总阻变化(total resistance shift)..... $\pm 2\%$ maximum 旋转寿命(rotational life) (no load).....1,000,000 shaft revolutions 总阻变化(total resistance shift)..... $\pm 5\%$ maximum 防潮性(moisture resistance) (mil-std-202, method 103, condition b) 总阻变化(total resistance shift)..... $\pm 2\%$ maximum 防护等级(ip rating) 密封对象 (sealed versions) (-3, -4, -7, and -8)ip 65 不密封对象(unsealed versions) (-1 -2, -5, and

-6).....ip 40 机械特性(mechanical characteristics) 终端止档强度 (stop strength).....45 n-cm (64 oz.-in.) minimum 机械角度(mechanical angle).....3600 ° +10 ° , -0 ° 扭矩(torque) (starting & running).....0.35 n-cm (0.5 oz.-in.) maximum (unsealed) 1.1 n-cm (1.5 oz.-in.) maximum (sealed) 固定方式(mounting).....55-80 n-cm (5-7 lb.-in.) (plastic) 90-113 n-cm (8-10 in.-lb.) (metal) 轴摆度(shaft runout).....0.13 mm (0.005 in.) t.i.r. 横向摆动(lateral runout).....0.20 mm (0.008 in.) t.i.r. 轴端游隙(shaft end play).....0.25 mm (0.010 in.) t.i.r. 转轴径向跳动(shaft radial play).....0.13 mm (0.005 in.) t.i.r. 引导径向跳动(pilot diameter runout).....0.08 mm (0.003 in.) t.i.r. 侧隙(backlash).....1.0 ° maximum 重量(weight).....approximately 19 g 终端设备(terminals).....solder lugs or pc pins 浸焊条件(soldering condition) 手焊(manual soldering).....96.5sn/3.0ag/0.5cu solid wire or no-clean 活性松香焊锡丝(rosin cored wire); 370 ° c (700 ° f) max. for 3 seconds 波动焊接(wave soldering).....96.5sn/3.0ag/0.5cu solder with no-clean flux; 260 ° c (500 ° f) max. for 5 seconds 清洗过程(wash processes).....not recommended 标记(markings).....manufacturer ' s name and part number, resistance value and tolerance, linearity tolerance, wiring diagram, and date code. 机械连接(ganging)(multiple section potentiometers).....1 cup maximum 五金器具(hardware).....one lockwasher and one mounting nut is shipped with each potentiometer.

本产品的加工定制是是，品牌是BOURNS/邦思，型号是电3590S-2-202L，种类是多圈，用途是精密，材料是玻璃釉膜，性能是微调，阻值调节方式是旋转式，阻值变化方式是X式（直线式），标称阻值是2k，额定功率是0.5（W），阻值允许偏差是±10（%），滑动噪声是0（V），分辨率是1（%），零位电阻是2（ ），接触电阻是1（ ），绝缘电阻是2（M ），符合度是100，温度系数是±50%