

1	tda - 400	400	1	50	380	0~650	615	109	10000	1523
2	tda- 400/6	400	1	50	6000	0~6300	63.5	9.3	10600	1733
3	tda- 400/6	400	1	50	10000	0~10500	38.1	5.8	11200	1733
4	tda- 450	450	1	50	380	0~650	692	122	10700	1523
5	tda- 450/6	450	1	50	6000	0~6300	71.4	10.5	11500	1733
6	tda- 450/10	450	1	50	10000	0~10500	42.8	6.5	12800	1733
7	tda- 500	500	1	50	380	0~650	769	132	11800	1523
8	tda- 500/6	500	1	50	6000	0~6300	79	11.2	12500	1733
9	tda- 500/10	500	1	50	10000	0~10500	47.6	7.1	13200	1733
10	tda- 630	630	1	50	380	0~650	969	165	14000	1733
11	tda- 630/6	630	1	50	6000	0~6300	100	13.6	15000	2153
12	tda- 630/10	630	1	50	10000	0~10500	60	8.8	16000	2153
13	tda- 800	800	1	50	380	0~650	1231	200	17000	
14	tda- 800/6	800	1	50	6000	0~6300	127	17	18000	
15	tda- 800/10	800	1	50	10500	0~10500	76.2	10.6	19000	
16	tda - 1000	1000	1	50	380	0~380	1538	243	20000	
17	tda- 1000/6	1000	1	50	6000	0~6300	159	20.6	21200	
18	tda- 1000/10	1000	1	50	10500	0~10500	95.2	12.8	22400	
19	tda- 1250	1250	1	50	380	0~380	1923	298	23600	
20	tda- 1250/6	1250	1	50	6000	0~6300	198	25.3	25000	
21	tda- 1250/10	1250	1	50	10500	0~10500	119	15.7	26500	
22	tda- 1600	1600	1	50	380	0~380	1421	212	31500	
23	tda- 1600/6	1600	1	50	6000	0~6000	147	18	33500	
24	tda- 1600/10	1600	1	50	10500	0~10500	88	11.2	35500	

序号	型号	额定输出容量 (kva)	相数	频率 (hz)	输入电压 (v)	输出电压范围 (v)	额定输出电流 (a)	空载电流 (a)	总损耗 (75) (w)	外形尺寸 长×宽 (cm)
1	tsa - 630	630	3	50	380	0~650	560	95	16000	1583
2	tsa- 630/6	630	3	50	6000	0~6300	57.7	8	17000	1583
3	tsa- 630/10	630	3	50	10000	0~10500	34.6	5	18000	1583
4	tsa - 800	800	3	50	380	0~650	711	115	19000	1733
5	tsa- 800/6	800	3	50	6000	0~6300	73.3	9.8	20000	2153
6	tsa- 800/10	800	3	50	10000	0~10500	44	6.2	21200	2153
7	tsa - 1000	1000	3	50	380	0~650	888	140	22400	1733
8	tsa- 1000/6	1000	3	50	6000	0~6300	91.6	11.8	23600	2153
9	tsa- 1000/10	1000	3	50	10000	0~10500	55	7.5	25000	2153
10	tsa - 1250	1250	3	50	380	0~650	1110	175	26500	2153
11	tsa- 1250/6	1250	3	50	6000	0~6300	115	14.5	28000	2153
12	tsa- 1250/10	1250	3	50	10000	0~10500	68.7	9.3	30000	2153
13	tsa - 1600	1600	3	50	380	0~650	1421	212	31500	2153
14	tsa- 1600/6	1600	3	50	6000	0~6300	147	18	33500	
15	tsa- 1600/10	1600	3	50	10000	0~10500	88	11.2	35500	
16	tsa - 2000	2000	3	50	380	0~380	1776	257	37500	
17	tsa- 2000/6	2000	3	50	6000	0~6300	183	21.7	39500	

18	tsa- 2000/10	2000	3	50	10000	0~10500	110	13.8	41800	
19	tsa - 2500	2500	3	50	380	0~380	2220	315	45000	
20	tsa- 2500/6	2500	3	50	6000	0~6300	229	26.6	47000	
21	tsa- 2500/10	2500	3	50	10000	0~10500	137	16.9	50000	
22	tsa - 3000	3000	3	50	380	0~380	2665	368	53000	
23	tsa- 3000/6	3000	3	50	6000	0~6300	275	31	56000	
24	tsa- 3000/10	3000	3	50	10000	0~10500	165	20	59000	

批发说明

本产品的电源相数是三相，额定功率是630-3000，防潮方式是开放式，冷却方式是自然冷式，冷却形式是干式，频率特性是低频，品牌是繁珠，绕组形式是自耦，铁心形式是壳式，铁心形状是E型，外形结构是立式，效率()是98%，型号是TDATSA，加工定制是是，应用范围是自耦