

Capacitor Running Start

产品名称	Capacitor Running Start
公司名称	安徽赛福电子有限公司
价格	3.50/个
规格参数	品牌:赛福saisu/sf 型号:CBB60runningstartcapacitors 介质材料:充气
公司地址	铜陵市 狮子山经济开发区 栖凤路1771号
联系电话	86-5626863178

产品详情

anhui safe electronics co., ltd.is a member of green international group. we mainly deal with ac motor capacitors, bopp film (polypropylene film), mpp film (metalized film), inkjet packing film, pet film and other related products.

1.features: cbb60 running start capacitor 14uf

the capacitor takes heavy-edge metallize al/zn pp film as electrodes and dielectric. its components are sealed with flame-retardant epoxy resin. it has cylindrical outline with high moisture resistance and stability.applicationsbroadly applied to starting and running of ac single-phase motors at 50hz(60hz) frequency for washers and high efficiency compressors of refrigerators etc.

technical specificationsstandard: iec 60252-1:2001technical features:climate type:40/70/21 or 40/85/21capacitance tolerance: $\pm 5\%$ insulation resistance: 3000s (m uf)

dielectric dissipation factor : tg 0.002 (50hz ~ 100hz)application requirements:altitude: 2000mresidual voltage in application :less than 10% of rated voltage.allowed maximum voltage: less than 1.1 times of rated voltagepermissible maximum current: less than 1.3 times of rated current

technical specifications :

额定电压 (vac)	标称电容量 (uf)	尺寸 (mm)	
		直径 (d)	高 (h)
450v	4 uf	26、35	52、68

5 μ f	26、 35	52、 68
8 μ f	35、 42	55、 80
10 μ f	35、 42	68、 80
20 μ f	42、 50	80、 100
25 μ f	42、 50	80、 100
30 μ f	42、 50	90、 100
45 μ f	50	100、 105
50 μ f	50	100、 105
60 μ f	50	100、 107

customized dimensions and specifications are available upon request

2.the company pictures show

the contact:miss ding

self phone:13305620325

q q:2437209049

fax:0562-2855972

company : anhui safe electronics co.,ltd

adress:no.1771 ofqifeng road , shizishan economic development zone, tongling city,anhui province,china

本产品的品牌是赛福saisu/sf，型号是CBB60runningstartcapacitors，介质材料是充气，应用范围是低压，外形是圆柱形，功率特性是中功率，频率特性是低频，调节方式是固定，引线类型是径向引出线，允许偏差是 ± 5 （%），耐压值是450（V），等效串联电阻(ESR)是ESR 5m（m），标称容量是14（uF），损耗是tg 0.002(50Hz~100Hz)，额定电压是450（V），绝缘电阻是 3000S（m），温度系数是40/70/21或40/85/21