

# PM Filter Coupler Module

产品名称	PM Filter Coupler Module
公司名称	绵阳慧联光通信设备有限公司
价格	1.00/只
规格参数	品牌:cofiber
公司地址	四川省绵阳市涪城区长虹大道南段83号
联系电话	0816-2384466-802 18190011210

## 产品详情

pm filter coupler module

**pm filter coupler module**

## features

low insertion loss

## applications

edfa & raman amplifier

high return loss

fiber sensor

a

high extinction ratio

fiber optical instrument

high reliability

power monitoring system

high stability

## specifications

### paramter

### unit

### value

type

-

1x3

center wavelength

nm

1310,1550

1064

operating wavelength range

nm

± 30

max. insertion loss		db	6.4	6.9
min.wdl		db		0.5
uniformity		db		0.8
min. extinction ratio	both of axis working	db	20	
	fast axis blocked	db	22	
min. return loss		db		50
directivity		db		50
temperature dependent loss		db/		0.006
max. optical power(cw)		mw		300
max. tensile load		n		5
fiber type	-			pm panda fiber
operating temperature				-5~+70
storage temperature				-40~+85
package dimensions		mm		100x80x1

for device with connector, il is 0.3db higher, rl is 5db lower, er is 2db lower;

the default connector key is aligned to slow axis;

package dimensions

ordering information

pmfcm-1111-2345-66

1111 -center wavelength: 1550=1550nm,1310=1310nm,.....,0850=850nm

2 -port number: 2=1x2, 3=1x3,....., 6=1x6

3 -axis alignment: f=slow axis working, fast axis blocked, b=both axis working

4 -pigtail type: 0=250 bare fiber, 1=900um loose tube, 2=2.0mm loose tube, 3=3.0 loose tube

5 -fiber length: 0=0.8m,1=1m

66 -connector type: 0=fc/upc,1=fc/apc,2=sc/upc,3=sc/apc,4=lc/upc,5=lc/apc

n style="mso-spacerun:'yes'; font-family:新宋体; color:rgb(0,0,0); font-size:10.5000pt; mso-font-kerning:1.0000pt; ">-fiber length:

0=0.8m,1=1m

66

-connector type:

0=fc/upc,1=fc/apc,2=sc/upc,3=sc/apc,4=lc/upc,5=lc/apc