

美国EIT通用型单通道UV能量计UVICURE PLUS II

产品名称	美国EIT通用型单通道UV能量计UVICURE PLUS II
公司名称	深圳市德胜兴科技有限公司
价格	11000.00/个
规格参数	加工定制:否 品牌:EIT 型号:UVICUREPLUSII
公司地址	深圳市宝安区沙井镇步涌新村大润科技大厦507
联系电话	0755-36887911 15989862032

产品详情

美国eit单通道 uv能量计eit uvicure plus ii

美国eit uvicure plus ii单通道能量计 屏幕同时显示强度值，能量值，温度的多功能uv能量计。可以挑选uva,uvb,uvc,uvv,uva2任一单波段型号。 specifications:

display	easy to read, yellow text on black background
suggested dynamic ranges	10 watt: uva, uvb, uvv - 100mw/cm ² to 10w/cm ² uvc - 50mw/cm ² to 1w/cm ² low power versions: uva, uvb, uvc, uvv: 1mw/cm ² to 100mw/cm ² *please note that units will run on at irradiance values lower than the suggested operating ranges.
accuracy	+/- 10%; +/- 5% typical
spectral ranges (uv power puck?ii)	4-channel simultaneous and continuous monitoring. 320-390nm (uva), 280-320nm (uvb), 250-260nm (uvc), 395-445nm (uvv)
spectral ranges (uvicure?plus ii)	1-channel continuous monitoring. 320-390nm (uva), 280-320nm (uvb), 250-260nm (uvc), 395-445nm (uvv)
spatial response	approximately cosine
operating temperature	0-75internal temperature; tolerates high external temperatures for short periods (audible alarm indicates

	when temperature has exceeded tolerance)
time-out period	2 minutes display mode (no key activity).
battery	two user-replaceable aaa alkaline cells
battery life	approx. 20 hours with display on
dimensions	4.60 x 0.50 inches; 117 mm x 12.7 mm (d x h)
weight	10.1 ounces (289 grams)
package material	aluminum, stainless steel
carrying case material	cut polyurethane interior, scuff resistant nylon exterior cover
carrying case weight	9 ounces (260 grams)
carrying case dimensions	10.75 x 3.5 x 7.75 inches; 274 x 89 x 197 mm (w x h x d).

本产品的加工定制是否，品牌是EIT，型号是UVICUREPLUSII，测量范围是100W，准确度是0.01，外形尺寸是117mmx12.7mm(DxH) (mm)，重量是0.289 (kg)，分辨率是0.01