

三辊压光机 台州宇绅 ACP1600

产品名称	三辊压光机 台州宇绅 ACP1600
公司名称	台州宇绅机械有限公司
价格	面议
规格参数	品牌:台州宇绅 型号:ACP1600 产品别名:压延机
公司地址	台州市君悦大厦A幢1311室
联系电话	13566883189

产品详情

model: acp -2000-06

framework components: steel-panel groove and steel machine chassis, to meet the need of the intensity and rigidity

rollers: 450 mm x 2,200 mm x 3sets

we adopt double helix laminas return back

to make the steady temperature of the rollers, and the temperature can rise or fall quickly without any cooling set. the surface of the roller quenching, rubbing, mirror polishing chromium plating treatment, then the rigidity can reach above hrc62. the rollers' surface deviation less than 0.02mm, temperature within ± 2 . the gyration connector of hot kerosene and tubes are with heat-resistant and press-resistant.

the orientation of rollers: use the exactitude pole elevator and its components. when the centre roller is fixed, then the up and bottom gap motors can be generally regulated, handfine adjustment, and modulated left and right independently. we can adjust quickly and fine adjustment at the same time. with the high intensity and precision, the improved design is the core centre for the acp quality.

the drive motor: 2.2kw x 3sets, independently transfer, and can adjust the speed by the material of pe and to improve the quality during the calendaring, glazing and equally extruding of the material.

line speed: 0.4 ~ 4 m/min

cooling transportation shelf: moulding groove and steel shelf

conveying rubber wheel: high-temperature and wear-resistant, 60mm x 1,800mm x 10sets

型号：acp-2000-06

机械重量：3,200 kg（大约）

架构组成：钢板槽钢机座，确保强度，刚性的需求。

整平轮组：500 mm x 2,200 mm x 3支

采用双套管螺旋叶片回路，使辊轮表面温度均匀，升/降温迅速，且无需大量冷却介质。辊轮表面淬火、研磨、镀硬铬后镜面抛光处理，硬度达到hrc62以上，辊轮表面跳动小于0.02mm，表面温度误差在±2以内。附热媒回转接头及耐热耐压软管。

轮组定位：采用精密丝杆升降机及其组件，中央轮固定，上、下轮间隙电机粗调，手动微调并可左右独立调整。可实现迅速调整间隙和高精度微调同时进行的目的。本机构高强度，高精度，优化后的设计是确保成品板材质量的核心部件。

传动马达：电机3.7kw

x3台，独立传动，可根据不同pe料做适度速度调整，使pe芯材压延，上光，均匀吐料质量显著提高。

线速度：0.4 ~ 4 m/min

本产品的品牌是台州宇绅，型号是ACP1600，产品别名是压延机，产品用途是塑料板材制作，辊筒数是三辊，辊筒工作直径是450（mm），辊筒线速度是2 - 6（m/min），生产能力是700（kg/h），外形尺寸是3200*1500*2000（mm），重量是4800（Kg），电动机功率是9（kw），压延厚度是1-6（mm），压延宽度是最宽2000（mm），售后服务是有，规格是2000，传动型式是三辊独立传动