

便携式数控切割机 便携式火焰切割机 终身免费升级

产品名称	便携式数控切割机 便携式火焰切割机 终身免费升级
公司名称	徐州铭德数控科技有限公司
价格	16800.00/个
规格参数	品牌:徐州铭德 型号:1525 类型:交流等离子焊机
公司地址	徐州市金山桥开发区宝莲寺路2号
联系电话	0516-87896193 13372226160

产品详情

整机配置

上海交大数控切割机专用系统

正版澳大利亚fast cam标准版套料软件（含加密狗）

深圳雷赛步进电机驱动器

日本信依步进电机

台湾亚德客电磁阀

日本和泉继电器

台湾明维开关电源

加强型铝合金横梁（包含内部氧气、燃气胶管，8芯控制线缆）

电动调高装置（包含24v直流减速电机）、万能割炬加持装置

氧气+燃气割炬总成（包含3路截止阀和3路电磁阀、隔热防护罩）

加厚高温定型整体工业铝合金导轨（含支撑轨枕）

纸箱+epe包装、说明书、合格证、装箱单

便携式数控火焰/等离子切割机

mingdeportable cnc flame/plasma cutting machine

型号model	md-1020	md-1225	
输入电源		220 ± 10%vac 50/60hz 220w	
power source			
切割方式		氧气/丙烷或乙炔；可配置等离子切割机	
cutting mode		o2/c3h8or c2h2, plasma available	
有效切割范围(宽 × 长)mm	1000 × 2000	1200 × 2500	
effective cutting range(mm)			
导轨 长 × 宽 × 厚mm	2500 × 273 × 60	3000 × 273 × 60	3000 × 273 × 60
track l × w × h(mm)			
配置的轨枕数量	2	3	
track holder quantity			
轨枕长 × 宽 × 厚mm		500 × 80 × 40	
track holder l × w × h(mm)			
切割速度mm/min		0-3500(最大4000)	
cutting speed(mm/min)		0-3500 (max 4000 available)	
切割厚度(火焰)mm		5-150(氧气+丙烷 或 乙炔)	
cutting thickness(flame)(mm)		5-150 (o2/c3h8or c2h2)	
切割厚度(等离子)mm		视客户等离子电源而定	
cutting thickness(plasma)(mm)		in terms of plasma power source	
运行精度		± 0.2mm/m	
move precision			
割枪和调高		火焰，电动调高(± 60mm)	
torch		flame,electric height adjustment(± 60mm)	
主机重量kg		19	
host weight(kg)			
整机重量	120	130	
total weight(kg)			
燃气压力mpa		最大0.1	
gas pressure(mpa)		max0.1	
氧气压力mpa		最大0.7	
oxygen pressure(mpa)		max0.7	
适用燃气种类		丙烷、乙炔	

type of gas	propane, ethine
急停按钮 emergency stop	有/yes
环境温度	-5 ~ 45
working temperature	
相对湿度	< 95% 无冷凝
relative humidity	< 95% no condensing

备注：*本产品在用户无特殊要求时，出厂标配统一为2号丙烷割嘴一个

standard configuration is 2#propane cutting nozzle if no special requirement.

*纵向导轨长度可按客户要求订制加长 tailor-made track if request.

功能说明

* 5.7寸高分辨率液晶显示屏，人性化操作界面，全中文/英文菜单，优化操作步骤，屏幕下方标注有操作提示，学。5.7 " high-resolution lcd, human-oriented interface, chinese and english menu, optimize operation procedure, tips under efficiency, flexibility, easy-going and easy learning.

* 7寸800*600高分辨率1600万色彩色高亮度液晶屏。

7" high-resolution lcd with 800*600pix,1600 color and high-bright.

*支持eia代码（即g代码）及fastcam等各类套料软件；中英文菜单，适合国内外各类操作人员。

support the eia code (g code) and all types of nesting software such as fastcam,etc. english and chinese menu system.

*自带45种常用图形库(包括网格图形)，可手工设置片尺寸和孔尺寸，直接切割，无需编程。

internal 45 types of basic figures(including the grid graphics), enable to setting piece size and pore size, directly do cutting programme.

*采用32位高性能cpu，运用实时多任务控制技术和dsp高速、高精度插补控制技术，工作时高稳定性，高速运行。

32 bits high speed and characteristics, multi-task controlling system and dsp high-speed, high-precision interpolation control increase stability and high speed with low noise.

*通用u盘传输g代码文件（切割轨迹文件），并可传输系统升级文件，使系统功能随时更新，方便快捷。

u-disk transfer g-code files(cutting track file), also able to transfer system upgrade files to guarantee the latest function to be in convenient and efficient.

* 256m超大容量存储空间，能存储超过5000个复杂异型切割文件；满足各种复杂程序的运行与加工，轻松处理大

256m large memory storage, could save more than 5,000 files; easily operating huge and multiple procedure.

*图型任意角度旋转、比例缩放、x或y镜像、矩阵排列、空走、可手工选行及选号等日常操作中的实用功能。

graphic scale, rotate, mirror image, matrix permutation, idling, select line or line number, etc, which will frequently be used.

*根据钢板厚度，在转角处可自动限速，有效防止过烧。支持边缘切割、偏移切割，对较厚的钢板可减少预热时间，避免因计算错误而造成的板材浪费。

automatically control the cutting speed to avoid over-burning according to plate thickness. possible to edge cutting, offset cutting of meal sheet caused by calculation errors.

*图形放大/缩小，放大状态下可实时跟踪切割点。自定义全部输入输出端口的类型（常开或常闭）和编号。

graphics zoom-in or out, and tracking the cutting point dynamically while zoom-in status. customize the type of all input and output port (normally open or close) and the number

*自诊断系统所有io状态和按键状态，方便检查和排除故障。单独或批量导入导出程序，参数备份及恢复，日期

self-diagnostic system for all io and keyboard status, convenient for inspection and trouble-shooting. export files, parameter upgrade; date, week and time display.

*支持氧燃气、等离子及演示模式；各类加工参数齐全，可满足不同工艺需求。

oxygen gas, plasma and presentation modes; various inside machining parameters for match various demand.

*氧燃气和等离子io分开控制；氧燃气自动调高，两级预热，三级穿孔；等离子弧压反馈，定位反馈，转角自动控制 oxygen gas from plasma io; adjust the height of oxygen gas automatically, two grades of preheat, three grates of voltage feedback, position feedback, automatically shut down arc voltage in the corner.

*断电、断点数据存储及恢复功能、退回功能、急停按钮，自动恢复到未断电前的状态，有效避免误操作。

auto-memory and recovery in case of power-off or point break, return function, emergency stop button, recover to the pre-state avoid mis-operation.

*高细分步进电机采用高细分驱动器，噪音低、精度高、运行平稳。

high-subdivision stepper motor driver, low noise, high running precision, and movement smoothly.

*自动割缝补偿，割枪移位，割枪穿孔停留，预热时间智能记忆，键盘诊断，温控风扇。标配电动高度调节装置。

cutting slot compensation auto-setting function , cutting gun movement, cutting gun perforation remain, preheated time auto-diagnostication, temperature-controlled fan. auto-adjust height of cutting gun and multiple torch clamp structure.

*稳定性强，具有超强的等离子高频抗干扰能力。*切割速度最大可调到每分钟3.5米，能满足快速等离子切割的

strong stabilization, effective shield plasma high frequency interference. max cutting speed 3500mm/min, apply to plasma cutting.

*机箱采用全钢防磁结构，完全屏蔽电磁辐射，真正抗干扰、防静电。

all steel and anti-magnetic outside frame of nc system and host to ensure reliable and stable operation.

*系统升级采用u盘升级方式，方便简单、实用，并提供终身免费升级服务。

free upgrade by u-disk easily and conveniently, and also provide free-upgrade at whole lifetime.

*特有钢板校正功能,任意钢板边可做为校正边;

steel board

adjustment function,each steel edge could be adjustable.

*图形可矩阵排列、交互排列、叠式排列。

graphic matrix permutation,alternate permutation,overlapping permutation

*工件原始尺寸和带割缝尺寸同时进行显示，直观方便。

display original size and size with cutting slot compensation at sametime, easy to control conveniently.

*等离子弧压控制支持速度和距离两种关闭弧压调高方式，使机床更加平衡、安全。

support speed and distance syle to close thc,to ensure more balance,stable and safety.

*最大程序行数the maximan lines of program.

*预留等离子切割机电源接口，可选配各种等离子切割机机型，弧压跟踪系统以及初始定位装置。

plasma cutting machine interface reserved; optionally set up all types of plasma cutting machine and arc voltage tracking system position and automatic arc voltage tracking system.

*选配:无线遥控器,可进行前、后、左、右等基本运作和切割开始、停止等切割动作。

徐州铭德数控科技有限公司

专业打造精工数控！卓越的产品！非凡的切割质量！超高的性价比！是您不二的选择！

销售热线：

0516-87896193、13382681866

本产品的品牌是徐州铭德，型号是1525，类型是交流等离子焊机，电流是交流，控制方式是数控，驱动形式是自动，用途是切割，频段是高频，作用对象是金属，作用原理是其他，动力形式是等离子，焊接原理是切割，是否提供加工定制是是，工作形式是数控火焰切割