

# ERS25-6屏蔽增压循环泵

产品名称	ERS25-6屏蔽增压循环泵
公司名称	温岭市易仕德机电有限公司
价格	面议
规格参数	品牌:EST 型号:ERS25-6 材质:铸铁
公司地址	温岭市大溪镇大溪岙村
联系电话	0576 86311119 13738690222

## 产品详情

应用屏蔽循环水泵专门用于供热系统。水泵也可适合于家庭生活热水循环和冷却器及空调系统的液体循环。

供热对于集中及区域供热系统，使用gr型号水泵。gr可以在三种速度下运行。水泵主要用于单管和双管的供热系统，但也适合于例如大系统中的温合回路。

地板供热对于地板供热系统，建议使用青铜gr型水泵，因为液体通常会汽化，会腐蚀普通铸铁水泵泵体。

生活热水可以与一个on/off定时开关相连以节能，on/off定时开关可发控制水泵的开/关从而保证水泵在需要热水时运行。冷却和空调系列对于冷却和空调系统，根据型号/尺寸，使用标准水泵gr型。application circulating water pump is dedicated to heating systems. hot water circulating pump can also be suitable for family life and cooler and liquid circulation of air conditioning system.

heating for central and district heating system, using gr model pump. gr can run under three kinds of speed. water

pump is mainly used in single tube and double tube heating system, but also suitable for large systems, for example temperature closed loop.

the floor heating for floor heating system, it is recommended to use bronze or type pumps, because usually vaporization liquid, corrosion of ordinary cast iron pump body.

living hot water can be connected to an on/off time switch to energy saving, on/off time switch can be sent to control water pump on/off to ensure the pump to run hot water. cooling and air conditioning series for cold and air conditioning systems, depending on the type/size, using standard type pump or.

本产品的品牌是EST，型号是ERS25-6，材质是铸铁，驱动方式是电动，性能是自动，用途是屏蔽泵，泵轴位置是边立式，叶轮结构是封闭式叶轮，叶轮数目是单级，叶轮吸入方式是单吸式，流量是50-460 (m<sup>3</sup>/h)，扬程是6-20 (m)，转速是2860 (r/m)，温度范围是0-110 ( )，重量是24 (kg)，规格是ERS25-6,ERS40-60(A),ERS40-60(B),ERS25-8,ERS25-8-180,ERS40-10-180,ERS25-15-180,ERS32-15-180,ERS40-370,ERS40-550,ERS40-750,ERS40-1100,ERS50-1500