

立式搅拌机，塑料搅拌机

产品名称	立式搅拌机，塑料搅拌机
公司名称	东莞市恩必信塑胶机械有限公司
价格	13501.00/台
规格参数	搅拌机类型:多功能搅拌机 应用领域:通用 物料类型:通用
公司地址	东莞市常平镇陈屋贝工业区牛路吓路6号
联系电话	0769-82784606

产品详情

立式搅拌机

Vertical Mixer

特点：

Features：

占地少，容量大，耗电低，省人工，混合均化快捷

It occupies less space, has large capacity, low power consumption, labor saving and uniform mixing

自动运转计时，马达过载保护，加料限位报警（选配）

Automatic operation time, motor overload protection, feeding limit alarm (optional)

设备与原料所接触部分的材料均为不锈钢制作，清料容易不易生锈

The materials in the parts in contact with the raw materials are made of stainless steel, and the materials are easy to rust

日本NSK轴承，采用内置式或分离式安装方式，使原料或粉末与轴承分离，不易卡死，大大延长轴承使用寿命

Japan NSK Bearings, using built-in or separate installation, so that the separation of raw materials or powder and bearings, is not easy to get stuck, greatly extend bearing life

工作原理：立式搅拌机的工作原理是螺杆的快速旋转将原料从桶体底部由中心提升至顶端，再以伞状飞抛散落，回至底部，这样原料在桶内上下翻滚搅拌，短时间内即可将大量原料均化的混合完毕

Working principle : The working principle of the vertical mixer is that the rapid rotation of the screw raises the material from the bottom of the barrel from the center to the top. And then throw the material in a manner of umbrella shape to the bottom. The materials are mixed up and down in the bucket in a short time

用途：塑料片料、粉碎料、塑料粒料、塑胶新旧料及添加色母搅拌均匀化等用途

Use : Plastic materials, regrind, plastic pellets, plastic masterbatch mixing old and new materials are added and so on purpose

适用行业：切粒、塑胶造粒、色母制造、塑料改性、再生料回收加工、大件注塑等行业

Applicable industry : Cutting, plastic granulation, color masterbatch manufacturing, plastic modification, recycled material recycling processing, large-scale injection molding and other industries

立式加热搅拌机

Vertical Heating Mixer Series

搅拌干燥同步：由于物料在进行干燥过程中，持续保持流动状态。热量渗透均化。干燥时间短且不易结块。

Stirring and drying synchronization : Since the material is kept in a flowing state during the drying process, the heat is uniformly penetrated, the drying time is short, and it is not easy to agglomerate

本系列标准机型为：双层桶体设计（经济型为单层设计）内层与物料接触部分全部为不锈钢材料制造，中央夹层安装特殊保温材料，因而可达到安全、节能的效果

The standard models of this series are : double-drum design(economical single-layer design), the inner layer and material contact parts are all made of non-induced steel materials; the middle interlayer is equipped with special insulation materials, which can achieve safety and energy saving effect

特制高频加热器，加热快，耗电少，每顿料干燥综合成本为25-30元，（含水1%以下，PP造粒料测试，0.9元/度电费计算，使用ABT-10R型测试

Special high-frequency heater, fast heating, low power consumption, the comprehensive cost of drying each material is 25-30 yuan. (Aqueous 1% or less, PP granulation test, yuan /kwh electricity cost calculation, using ABT-10R type test)

特设双管排湿口，能有效排出湿气，收集粉尘，绝不污染工作环境

The special double-tube drainage port can effectively discharge moisture, collect dust, and never pollute the working environment

桶体设有入口门（选购）换色换料清理简单快捷

The barrel body is provided with an entrance door (optional), and it is quick and easy to change color and refuel

型号多，容量大，常备一次性能装载：0.5吨、1吨、1.5吨、2吨、3吨等现货供客选用

There are many models and large capacity, and one performance load is available: 0.5 tons, 1 ton, 1.5 tons, 2 tons, 3 tons, etc

干燥混合功能二合一，当不需要干燥时，只需将“加热开关”及“风机开关”关闭，本系列机型即可用于塑料搅拌均化用途，一机二用。

The dry mixing function is two-in-one, When it is not necessary to dry, just turn off the “heating switch” and “fan switch”. This series of models can be used for plastic mixing and homogenization purposes, one machine and two