

振动耐磨试验机

产品名称	振动耐磨试验机
公司名称	东莞市东日仪器有限公司
价格	9800.00/个
规格参数	加工定制:是 品牌:tohnichi/东日 型号:TE-30
公司地址	广东东莞市东莞市厚街镇大唐村133号
联系电话	86 0769 85082180 13925789605

产品详情

te-30rosler振动耐磨试验机

nokia指定专用的手机表面涂层耐磨擦试验机. 用于测试手机之外壳耐磨性.

nokia指定专用振动耐磨试验机的详细说明:通过将产品放进彩色石子和药水混合的特殊液体中,进行振动磨擦,测试产品的耐磨擦性能.型号 : trough vibrator r180/530 te-30主机 : trough vibrator r180/530

te-30 (内置switch unit e51-0,65 和metering unit d1-4) 配套辅料 : 1.绿色磨粒rkk 15p 25kg (客户自配) 2.黄色磨粒rkf 10k 75kg (客户自配) 3.测试药水fc120 30kg (客户自配)

制造商 : 东日m03d06kp1rosler trough vibrator r 180/530 te-30processing trough:处理槽a. stable, vibration-resistant weldment with special ribbing专用加强筋做的,稳定的,防振的焊件b. stress-free annealed welding construction无应力的退火焊接结构c. lining of the processing trough:hot-casted polyurethane处理槽里的衬套是热铸的聚亚安酯(一种在韧性上差别很大的树脂,用于坚固的抗化学物质涂面、黏合剂和泡沫中)d. thickness:10mm厚度: 10mme. dimensions of the trough: d: 180mm l:530mm槽的尺寸: 深: 180mm 长: 530mm

machine frame:机器的框架a. stable weldment with seat for the trough带支座的槽,稳定的焊件b. processing trough situated on helical springs处理槽位于螺旋状的弹簧上machine drive:机器的驱动a. drive by 1 electric motors situated under the trough位于槽下的一个电动马达来驱动b. power: 1x0.65kw功率: 1x0.65kwc. speed:3000rpm转速: 3000rpm d. voltage:230/400 v.3ph n/pe.50hz电压: 230/400 v.3ph n/pe.50hc2203100switch unit e51-0.65开关部分designed for the vibro-finishing processa. combined on/off-main switch组合的打开关闭主开关b. on/off tip button for processing speed对处理速度有打开关闭末端按钮c. overload protection for processing speed对处理速度有过载保护d. timer for processing time对处理时间有定时器e. connection possibility for the metering unit对测量部分有连接可能性f. triggering of a driver motor由驱动器马达触发g. coloration:ral 7032 pebble grey着色: ral 7032 卵石灰白h. standard operation voltage:400/230 v.50hz,3ph n/pe标准运转电压: 400/230 v.50hz,3ph n/pei. standard control voltage:230v 50hz标准控制电压: 230v 50hzj. degree of protection:ip 54保护等级: ip 54k. ambience temperature +5up to +40 deg.celsius周围环境温度: 摄氏 +5 ~ +40 °

m1601008metering unit d1-4测量部分 d1-4a. for dosing weter-compound mixtrueb. dosing quantity can be stepless adjusted from 0-4 l/h定量给料量在0-4 l/h范围内能被无级

更多关于仪器资料，欢迎来电来人咨询洽谈，

联系人；丁平 电话；13925789605 0769-85082180 传真 0769-85054726

邮箱 dingping0229@163.com ，网站；www.dongritest.com

qq 2242349384

本产品的加工定制是是，品牌是tohnichi/东日，型号是TE-30，测量范围是30，磨擦频率是50，测量行程是180（mm），机台尺寸是180-530（mm）