

## CASTROL OPTILEB GT 680 ;

产品名称	CASTROL OPTILEB GT 680 ;
公司名称	深圳市吉顺达润滑油有限公司
价格	1.00/桶
规格参数	品牌:嘉实多 型号: CASTROL OPTILEB GT680
公司地址	深圳市龙华新区大浪办事处高峰社区下早新村133号202室（办公场所）
联系电话	0755-23092526 18926754019

## 产品详情

????????? > ??? > CASTROL OPTILEB GT680,CASTRO

---

Zusammensetzung bleiben vorbehalten, gegebenenfalls in Absprache mit dem Kunden. Weitere Produkt-Informationen sind bei der BP Aktiengesellschaft zu erfragen. Deutsche BP AG – Industrial Lubricants & Services, Erkelenzer Str. 20, 51043 Erkelenz, Tel. (0)2161 909-481 www.castrol.com/industrial Page 2 of 2 Technical data Unit Value Test method CASTROL OPTILEB GT 680  
yellow visual Base - polyalphaolefin - ISO viscosity group - 100 150 220 320 460 680 DIN 51519 Density at 15°C  
Kin. viscosity at + 40°C/+ 104°F at + 100°C/+ 212°F mm<sup>2</sup>/s 101 14.5 149.0 19.4 213 26.3 320.1 34.2 465 49.5  
151 143 DIN ISO 2909 Pour point °C °F - 42 - 43.6 - 42 - 43.6 - 39 - 32.8 - 36 - 27.4 - 36 - 16.6 - 27 - 5.8 DIN ISO 2909  
234 453.2 249 480.2 240 464 DIN ISO 2592 Copper corrosion protection - 1a 1a 1a 1a 1a 1a ASTM D-130  
DIN 51355 FZG test (8.3/90) Scoring load stage - > 12 > 12 > 12 > 12

### **CASTROL OPTILEB GT680,CASTROL OPTILEB GT 680 ??**

CASTROL OPTILEB® GT™ Fully synthetic gear lubricants, physiologically safe, NSF H1 authorized for food and beverage applications, especially developed to meet the special requirements in the food and beverage industries. Contains selected additives to prevent wear, oxidation and corrosion. OPTILEB® GT gear oils are in conformity with the following standards:  
APPLICATIONS · For the special requirements in the food and beverage industries where there may be direct contact with foodstuffs · For packaging · For spur, angular and worm gears · For gear motors of stirring machines, turners, packaging machines, etc.  
bearings · For pumps and closed circulating systems ADVANTAGES · OPTITEC® - OPTIMOL technology · excellent wear, oxidation and corrosion protection · good water separation ability · no foam formation · excellent viscosity/temperature behavior · miscible with mineral oil · disposal like mineral oil NOTES FOR USE · Please read the instructions for use carefully.  
Good compatibility with conventional sealing materials. · As OPTILEB® GT is miscible with mineral oils, a gradual conversion is possible.  
Product Data Optileb GT 23.02.2007 Castrol Optileb GT and Castrol logo are trademarks of Castrol. Die angegebenen Werte sind Durchschnittswerte, die jedoch innerhalb der festgelegten Spezifikation liegen. Diese Angaben entsprechen den üblichen Anforderungen an die Vielfalt der Anwendungen kann daraus keine Verbindlichkeit für die Bewährung in jedem Einzelfall hergeleitet werden.