

## 专业生产smc.dmc.玻璃钢电表箱

产品名称	专业生产smc.dmc.玻璃钢电表箱
公司名称	河南双同电气有限公司
价格	面议
规格参数	品牌:双同 型号:6户左右电表箱
公司地址	西平县迎宾大道东段南侧
联系电话	17737387512

## 产品详情

smc.dmc材质电表箱有八大优势一、良好的耐腐蚀性能 it possesses sound decay resistance 可有效抵抗水、汽油、酒精、电解盐、醋酸、钠钾化合物、沥青、各种酸碱土壤及酸雨的腐蚀。产品本身具有良好的抗老化性能，制品表面具有一层耐紫外线能力极强的防护层，双理防护制品具有更高的抗老化性能。 it will effectively resist corrosion of water ,petor,alcohol,electrolysis salt, ethylic acid, sodium and potassium compound,asphalt,various acid-base soil and acid rain, product itself owns sound ageing resistance property and its surface is protected by strong uv resistance layer as well as double protection product is bestowed with better ageing resistance property. 二、是一种无烟无毒材料 it is a smokeless and non-toxic material 不含卤素，无对人体有害物质，灼烧时不产生有害气体，是一种环保材料，满足未来发展需要。 it is free from halogen and harmful substance and will not produce detrimental gas while being burnt, thus making it an environmental friendly material and can satisfy future development requirements. 三、箱体采用板式结构组合 combined plate-type structure shall be adopted for the box. 模块化安装，适于搬运，安装简单，可现场组装和拆卸。柜体表面铸有菱形突起，有防止小广告粘贴的功能。 modularization installation, which is suitable for carrying and easy to be installed, can be assembled and dismantled on site. cabinet surface is cast with prominence,whith makes it free from sticking adlets. 四、适合各种恶劣天气 it is suitable for severe weather 可长期使用在-50—160摄氏度环境中，防护等级ip55 it can be used in the environment of -50—160 with protection of ip55. 五、优异的绝缘材料 excellent insulating material. 高性能的绝缘电阻防止漏电，在高频下能保持良好的介电性能，不反射，阻断微波的传播不生锈可长期使用，适用于人流密集或狭窄场所，避免人体触电现象。 high insulation-resistance performance can prevent leakage of electricity,maintain sound electrical property under high frequency,and not reflex and block transmission of microwave as well as can be used for a long time without rueting,thus making it suitable for crowded or narrow place and prevent people from electric shock. 六、三维网状分子结构和增强纤维共同作用 combined action of three-dimensional network molecule and reinforced fiber 该材料具有良好的抗冲击性，易于机械加工，便于钻孔、利于切割、定位准确。具有很高的拉伸强度，变曲模量和冲击韧性。 this material, possessing favorable impact resistance,is easy to be processed and convenient to be drilled,cut and correctly positioned.what ' s more,it owns high tensile strength,bending modulus and impact toughness as well. 七、阻燃材料 fire-retardant material 阻燃性能可达到fvo级，烟密度等级为15，烟气毒性等级为准安全一级（zai）。所有材料满足国内外最好ul94要求。 flame retardant property is able to reach fvo grade,and smoke density grade is of 15,as well as grade of smoke toxicity is zai.this material satisfies the best ul94 requirements at home and abroad. 八、是一种热的不良导体 a non-

conductor of heat 耐高温、热变形率低，可降低环境温差对箱体内部的影响，同金属材料相比可有效减少箱体内部凝露和凝霜。 it can resist high temperature,own low thermal deformation rate,and reduce effect of difference in environmental temperature on the interior part of box,thus making it effectively reduce condensation and frost of the interior part of box comparing with the metallic material.